



Revision Number: 004.0

Issue date: 08/02/2019

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>LOCTITE ECCOBOND CB064 known as 10CC LOW STRESS ENCAP -40CD</b>	<b>IDH number:</b>	549327
<b>Product type/use:</b>	Encapsulant	<b>Item number:</b>	CB064-V24
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

This product contains an epoxy resin CAS # 27610-48-6 that is covered by a USEPA Significant New Use Requirement (SNUR) (40CFR 721.5192) that limits its use to binding fibers in aerospace composites or for encapsulating electronic devices. It is a violation of the SNUR to use this product for any other application. Contains one or more components for which a Toxic Substances Control Act (TSCA) Low Volume Exemption (LVE) applies. See Section 15.

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**DANGER:** CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE IRRITATION.  
MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.  
MAY CAUSE RESPIRATORY IRRITATION.  
SUSPECTED OF CAUSING GENETIC DEFECTS.  
SUSPECTED OF CAUSING CANCER.  
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
GERM CELL MUTAGENICITY	2
CARCINOGENICITY	2
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

**PICTOGRAM(S)**



**Precautionary Statements**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate ventilation wear respiratory protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Silica, vitreous	60676-86-0	60 - 80
Silicon dioxide	7631-86-9	10 - 30
Hexahydromethylphthalic anhydride	25550-51-0	5 - 10
Oxirane, 2,2'-(1,6-naphthalenediylbis(oxy)methylene)	27610-48-6	5 - 10
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

**Symptoms:** See Section 11.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Water spray (fog), foam, dry chemical or carbon dioxide.

**Special firefighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.

**Unusual fire or explosion hazards:** Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

**Hazardous combustion products:**

Oxides of carbon. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**

Do not allow product to enter sewer or waterways.

**Clean-up methods:**

Remove all sources of ignition. Ensure adequate ventilation. Isolate area. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, saw dust). Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:**

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.

**Storage:**

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silica, vitreous	None	20 MPPCF TWA 0.8 mg/m <sup>3</sup> TWA	None	None
Silicon dioxide	6 mg/m <sup>3</sup> TWA	20 MPPCF TWA 0.8 mg/m <sup>3</sup> TWA	None	3 mg/m <sup>3</sup> TWA Respirable fraction.
Hexahydromethylphthalic anhydride	None	None	None	None
Oxirane, 2,2'-(1,6-naphthalenediyl)bis(oxy)methylene	None	None	None	0.1 ppm TWA
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. 4H gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:**

Viscous, Liquid

**Color:**

Black

**Odor:**

Little intrinsic odor

**Odor threshold:**

Not available.

**pH:**

Not applicable

**Vapor pressure:**

Not available.

<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.9
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	> 121.1 °C (> 249.98 °F)
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	Not available.
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Irritating organic vapours.
<b>Incompatible materials:</b>	Strong oxidizing agents. Strong acids and strong bases. Water, Amines, Alkalis, Alcohols. Mercaptans.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Store away from incompatible materials. Exposure to moisture. Heat, flames, sparks and other sources of ignition. High temperatures.

## 11. TOXICOLOGICAL INFORMATION

<b>Product toxicity data:</b>	The U.S. Environmental Protection Agency (EPA) has identified certain substances that are structurally similar to the epoxy resin component with CAS # 27610-48-6. These analogues are phenylglycidylether and diglycidylether of resorcinol. Based on the results of animal bioassays on these analogues, the EPA finds that the epoxy resin component (CAS # 27610-48-6) may be carcinogenic and may cause reproductive effects. The epoxy resin is expected to be absorbed via all routes.
<b>Relevant routes of exposure:</b>	Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

**Inhalation:** May cause respiratory tract irritation. May cause allergic respiratory reaction. Coughing. Wheezing. Shortness of breath.  
**Skin contact:** Causes skin irritation. May cause allergic skin reaction.  
**Eye contact:** Causes serious eye irritation. Prolonged contact may cause eye burns and corneal injury.  
**Ingestion:** May cause irritation to the gastrointestinal tract, mouth and mucous membranes.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silica, vitreous	None	Nuisance dust
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg	Nuisance dust
Hexahydromethylphthalic anhydride	None	Allergen, Respiratory, Irritant
Oxirane, 2,2'-(1,6-naphthalenediyl)bis(oxymethylene)	None	Irritant, Allergen, Blood, Reproductive
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silica, vitreous	No	No	No
Silicon dioxide	No	No	No
Hexahydromethylphthalic anhydride	No	No	No
Oxirane, 2,2'-(1,6-naphthalenediyl)bis(oxymethylene)	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Any process stream associated with the use of this product must be disposed of by incineration or in a landfill. This provision, however, does not supersede any applicable federal, state or local laws and regulations.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated (Up to 6 oz. max per inner/primary package when shipped as originally packaged only)  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated (Up to 6 oz. max per inner/primary package when shipped as originally packaged only)  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated (Up to 6 oz. max per inner/primary package when shipped as originally packaged only)  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** This product contains one or more components that are exempt from listing on the U.S. Toxic Substances Control Act (TSCA) inventory because a Low Volume Exemption (LVE) has been granted in accordance with 40 CFR 723.50. Quantities may be limited.

**TSCA 5 (a) (2) SNUR:** This product contains an epoxy resin CAS # 27610-48-6 that is covered by a USEPA Significant New Use Requirement (SNUR) (40CFR 721.5192) that limits its use to binding fibers in aerospace composites or for encapsulating electronic devices. It is a violation of the SNUR to use this product for any other application. Manufacture, import, distribution, use and disposition of this product is restricted to the requirements listed in 40 CFR.

**TSCA 12 (b) Export Notification:** Substituted 1,6-dihydroxy naphthalene (CAS# 27610-48-6).

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** None above reporting de minimis.

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

**CEPA DSL/NDL Status:** One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11,16

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 08/02/2019

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.