

Revision Number: 005.0

PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCT Product type/use: Encap Restriction of Use: None Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE ECCOBOND FP0087 Encapsulant None identified

1.

 IDH number:
 498413

 Item number:
 FP0087-V25A1

 Region:
 United States

 Contact information:
 Telephone: +1 (860) 571-5100

 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711

 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887

 Internet: www.henkelna.com
 Telephone: Poison Control Center

## 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
DANGER:	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE DAMAGE.
	MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING
	DIFFICULTIES IF INHALED.
	MAY CAUSE RESPIRATORY IRRITATION.
	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED
	EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

PICTOGRAM(S)

#### **Precautionary Statements**

Prevention:	Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate ventilation wear respiratory protection.
Response:	IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Take off contaminated clothing.
Storage: Disposal:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Silica, amorphous, naturally	60676-86-0	60 - 80	
hexahydromethylphthalic anhydride	25550-51-0	10 - 30	
Epoxy resin	Proprietary	5 - 10	
Limestone	1317-65-3	1 - 5	
Quartz (SiO2), <1% respirable	14808-60-7	1 - 5	
Epoxy resin	Proprietary	1 - 5	
Silicon dioxide	7631-86-9	1 - 5	
Substituted phthalic anhydride	34090-76-1	1 - 5	
Epoxy resin	Proprietary	0.1 - 1	

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. Fl	RST AID MEASURES
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Give a conscious person several glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.
5. FIRE	E FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	In case of fire, keep containers cool with water spray. Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors. Aldehydes. Phenolics. Hydrocarbons.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** 

Clean-up methods:

Do not allow product to enter sewer or waterways.

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during cleanup. Scrape up spilled material and place in a closed container for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8. Use only with adequate ventilation.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silica, amorphous, naturally	None	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
hexahydromethylphthalic anhydride	None	None	None	None
Epoxy resin	None	None	None	None
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None
Epoxy resin	None	None	None	None
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Substituted phthalic anhydride	0.0003 ppm STEL 0.00007 ppm TWA 0.7 mg/100 cm2 TLV- SL (SKIN) (Dermal sensitization) (Respiratory sensitization)	None	None	None
Epoxy resin	None	None	None	None

Engineering controls:

**Respiratory protection:** 

Eye/face protection:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Full face protection should be used if the potential for splashing or spraying of product exists. Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: IDH number: 498413

Liquid Black Aromatic Not available. Not applicable Not available.

Page 3 of 6

Boiling point/range:	Not ava
Melting point/ range:	Not ava
Specific gravity:	1.8
Vapor density:	Not ava
Flash point:	260 °C
Flammable/Explosive limits - lower:	Not ava
Flammable/Explosive limits - upper:	Not ava
Autoignition temperature:	Not ava
Flammability:	Not app
Evaporation rate:	Not ava
Solubility in water:	Insolubl
Partition coefficient (n-octanol/water):	Not ava
VOC content:	Not ava
Viscosity:	Not ava
Decomposition temperature:	Not ava

Not available. Not available. 1.8 Not available. 260 °C (500°F) Not available. Not available.

## **10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Aldehydes. Phenolics. Hydrocarbons. Irritating organic vapours.
Incompatible materials:	Oxidizing agents. Acids and bases. Amines. Alcohols. Water
Reactivity:	Not available.
Conditions to avoid:	Exposure to sunlight. Exposure to moisture. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

# **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation. May cause allergic respiratory reaction. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure). Contains crystalline silica (quartz), which is classified as a possible carcinogen. However, the crystalline silica present in this product is encapsulated in the liquid and will only be liberated if the product is sanded or abraded, and even then what is liberated will not be pure crystalline silica. Appropriate precautions, however, should be taken if the product is sanded to prevent personnel from breathing the dust.
Skin contact:	Causes skin irritation. May cause allergic skin reaction. Repeated or prolonged contact may cause burns. Pain and discomfort. Redness.
Eye contact: Ingestion:	Causes serious eye damage. Pain and discomfort. Blurred vision. Tearing. Redness. May cause gastrointestinal tract irritation if swallowed. May cause burns of mouth and throat if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silica, amorphous, naturally	None	Nuisance dust
hexahydromethylphthalic anhydride	None	Allergen, Respiratory, Irritant
Epoxy resin	None	Allergen, Irritant
Limestone	None	Nuisance dust
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity
Epoxy resin	None	Allergen, Irritant
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg	Nuisance dust
Substituted phthalic anhydride	None	Irritant, Allergen, Respiratory
Epoxy resin	None	Allergen, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silica, amorphous, naturally	No	No	No
hexahydromethylphthalic anhydride	No	No	No
Epoxy resin	No	No	No
Limestone	No	No	No
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
Epoxy resin	No	No	No
Silicon dioxide	No	No	No
Substituted phthalic anhydride	No	No	No
Epoxy resin	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

## **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

## **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Hazard class or division: Identification number: Packing group: Not regulated (Up to 2 oz. max per inner/primary package when shipped as originally packaged only) None None None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated (Up to 2 oz. max per inner/primary package when shipped a originally packaged only)
Hazard class or division:	None
Identification number:	None
Packing group:	None
r Transportation (IMO/IMDG)	
r Transportation (IMO/IMDG)	
r Transportation (IMO/IMDG) Proper shipping name:	Not regulated (Up to 2 oz. max per inner/primary package when shipped a
Proper shipping name:	originally packaged only)
• • • •	
Proper shipping name:	originally packaged only)

# **15. REGULATORY INFORMATION**

#### United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
	All second second second second second from the first second se

# **CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: 2, 3

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 01/11/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.