

# LINQTAPE PET2S-Green



## 2-mil Green Polyester Tape with Silicone Adhesive

- 2 mil green polyimide film
- Silicone adhesive
- 4200V breakdown voltage

**LINQTAPE™ PET2S-Green** is a 2-mil polyester film backing with a pressure sensitive silicone adhesive system. It is a no/low residue tape designed for splicing and masking applications where high initial adhesion is required, but no residue once the tape is removed.

**LINQTAPE™ PET2S-Green** comes in 66 meter (72 yard) rolls of varying widths. LINQTAPE PET-S polyester films with silicone adhesive are available in a range of thicknesses, starting from 1 mil (25.4µm) thickness and up. Custom thicknesses are available upon request.

### Specifications

Property	Value	Unit
Color	Green	-
Adhesive Type	Silicone	-
Film Thickness	50.8 (2)	um (mil)
Adhesive Thickness	38.1 (1.5)	um (mil)
Release liner	None	-
Total Thickness	88.9 (3.5)	um (mil)
Temperature Resistance	200	°C
Tensile Strength	50	lbs/in
Elongation	>100	%
Breakdown Voltage	7000	Volts
Peel Strength	30	oz/in
Insulation Class	180	(H)

### Storage and Handling

Shelf life is 2 years when stored in a dry, cool and well ventilated place at room temperature.

The product is supplied in rolls and should be kept in a cool (10°C – 25°C) dry place (40% – 75% humidity) away from direct sunlight or temperature extremes. Once removed from packaging it should be protected against dust and other impurities.

#### Europe

Industrieweg 15E,  
1566JN Assendelft  
The Netherlands  
Phone: +31 (20) 893 2224  
Email: info@caplinq.com

#### Canada

80 Sirocco Crescent  
Ottawa ON, K2S 2C9  
Canada  
Phone: +1 (613) 482-2215  
Email: info@caplinq.com



#### North America

36927 Schoolcraft Rd  
Livonia, MI 48150  
United States  
Phone: +1 (313) 558-8243  
Email: info@caplinq.com

#### South East Asia

S-08-07 Persiaran Triangle  
B Lepas, Penang 11900  
Malaysia  
Phone: +60 (12) 4302223  
Email: info@caplinq.com