

LINQTAPE ITO-125

125 μm Indium Tin Oxide film



- $\geq 76\%$ Light transmittance
- ± 5 ohm/square Surface resistivity
- 125 μm Thickness

LINQTAPE ITO-125 is a 125 μm film made out of Indium Tin Oxide (ITO) backed on a PET substrate. ITO-125 is a n-type semiconductor material, which offers a unique combination of properties that are useful for a wide range of applications. The high conductivity and anti-static properties of the film make it ideal for electromagnetic shielding applications, while the high transparency and thin film properties are great for PDP plasma color TV windows, computer displays, printers, and other electronic devices.

LINQTAPE ITO-125 has exceptional high visible light transmittance and low resistivity, making ITO conductive film one of the most versatile and high-performance conductive materials available.

Specifications

Property	Value	Unit
Surface resistivity	5 \pm 2	ohm/square
Transparency	≥ 76	%
Shielding performance	21db/30MHz~23db/1.5GHz	-
Temperature range	-60~+150	$^{\circ}\text{C}$
Thickness	125	μm
Haze	2.5 \pm 1	%
Adhesion	B	5B (ASTM D3359)
Hardness	H	-
Heat Shrinkage (MD)	≤ 0.8	%
Heat Shrinkage (TD)	≤ 0.3	%
Warpage	≤ 10	%

Storage and Handling

Shelf life is 2 years if stored in a dry and cool, well ventilated place at room temperature.

The product is supplied in rolls and should be kept in a cool (10 $^{\circ}\text{C}$ – 25 $^{\circ}\text{C}$) dry place (<65% humidity) away from direct sunlight or temperature extremes. Once removed from packaging it should be protected against dust and other impurities.

Europe

Industrieweg 15E,
1566JN Assendelft
The Netherlands
Phone: +31 (20) 893 2224
Email: info@caplinq.com

Canada

80 Sirocco Crescent
Ottawa ON, K2S 2C9
Canada
Phone: +1 (613) 482-2215
Email: info@caplinq.com



North America

36927 Schoolcraft Rd
Livonia, MI 48150
United States
Phone: +1 (313) 558-8243
Email: info@caplinq.com

South East Asia

S-08-07 Persiaran Triangle
B Lepas, Penang 11900
Malaysia
Phone: +60 (12) 4302223
Email: info@caplinq.com