



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 16

LOCTITE ABLESTIK ABP 6892

SDS No. : 541446
V003.0

Revision: 29.10.2019
printing date: 15.03.2021

Replaces version from: 04.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE ABLESTIK ABP 6892

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Die attach adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Acute toxicity	Category 4
H302 Harmful if swallowed. Route of Exposure: Oral	
Skin irritation	Category 2
H315 Causes skin irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Germ cell mutagenicity	Category 2
H341 Suspected of causing genetic defects. Carcinogenicity	
H351 Suspected of causing cancer.	Category 2

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Amines, C36-alkylenedi-, maleated

t-Butylcyclohexylpercarbonate
Epoxycyclohexylethyltrimethoxysilane**Signal word:**

Warning

Hazard statement:H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.**Precautionary statement:
Prevention**

P280 Wear protective gloves/protective clothing.

**Precautionary statement:
Response**P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**2.3. Other hazards**

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Amines, C36-alkylenedi-, maleated 682800-79-9		50- 100 %	Acute Tox. 4 H302 Acute Tox. 4 H312 Skin Irrit. 2 H315
t-Butylcyclohexylpercarbonate 15520-11-3	239-557-1 01-2119966122-42	1- < 5 %	Org. Perox. C H242 Skin Sens. 1 H317 Aquatic Chronic 4 H413
Epoxy cyclohexylethyltrimethoxysilane 3388-04-3	222-217-1	1- < 5 %	Skin Sens. 1B H317 Muta. 2 H341 Carc. 2 H351 Aquatic Chronic 3 H412
Toluene 108-88-3	203-625-9 01-2119471310-51	0,1- < 1 %	Flam. Liq. 2 H225 Repr. 2 H361d Asp. Tox. 1 H304 STOT RE 2; Inhalation H373 Skin Irrit. 2 H315 STOT SE 3; Inhalation H336 Aquatic Chronic 3 H412

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

In case of fire, keep containers cool with water spray.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Remove sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Die attach adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Toluene 108-88-3 [TOLUENE]	50	191	Time Weighted Average (TWA):		EH40 WEL
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):		EH40 WEL
Toluene 108-88-3 [TOLUENE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	Indicative	ECLTV

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Toluene 108-88-3 [TOLUENE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	aqua (freshwater)		0,39 mg/l				
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	aqua (marine water)		0,039 mg/l				
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	aqua (intermittent releases)		0,39 mg/l				
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	aqua (freshwater)				4685 mg/kg		
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	sediment (marine water)				468,5 mg/kg		
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	Soil				936,8 mg/kg		
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	sewage treatment plant (STP)		2 mg/l				
Toluene 108-88-3	aqua (freshwater)		0,68 mg/l				
Toluene 108-88-3	sediment (freshwater)				16,39 mg/kg		
Toluene 108-88-3	sediment (marine water)				16,39 mg/kg		
Toluene 108-88-3	Soil				2,89 mg/kg		
Toluene 108-88-3	sewage treatment plant (STP)		13,61 mg/l				
Toluene 108-88-3	aqua (marine water)		0,68 mg/l				
Toluene 108-88-3	aqua (intermittent releases)		0,68 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	Workers	inhalation	Long term exposure - systemic effects		5,87 mg/m ³	
Bis(4-tert-butylcyclohexyl) peroxydicarbonate 15520-11-3	Workers	dermal	Long term exposure - systemic effects		16,67 mg/kg	
Toluene 108-88-3	Workers	Inhalation	Acute/short term exposure - local effects		384 mg/m ³	
Toluene 108-88-3	Workers	Inhalation	Acute/short term exposure - systemic effects		384 mg/m ³	
Toluene 108-88-3	Workers	Inhalation	Long term exposure - local effects		192 mg/m ³	
Toluene 108-88-3	Workers	Inhalation	Long term exposure - systemic effects		192 mg/m ³	
Toluene 108-88-3	Workers	dermal	Long term exposure - systemic effects		384 mg/kg	
Toluene 108-88-3	General population	Inhalation	Acute/short term exposure - local effects		226 mg/m ³	
Toluene 108-88-3	General population	Inhalation	Acute/short term exposure - systemic effects		226 mg/m ³	
Toluene 108-88-3	General population	Inhalation	Long term exposure - systemic effects		56,5 mg/m ³	
Toluene 108-88-3	General population	dermal	Long term exposure - systemic effects		226 mg/kg	
Toluene 108-88-3	General population	oral	Long term exposure - systemic effects		8,13 mg/kg	
Toluene 108-88-3	General population	inhalation	Long term exposure - local effects		56,5 mg/m ³	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	paste
	clear
Odor	None
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	121 °C (249.8 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,05 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Strong oxidizing agents.

Strong bases.

Acids.

Reducing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if stored and applied as directed.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

Hydrocarbons

nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

General toxicological information:

Prolonged or repeated contact may cause eye irritation.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
t-Butylcyclohexylpercarbonate 15520-11-3	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Epoxy-cyclohexylethyltri-methoxysilane 3388-04-3	LD50	13.000 mg/kg	rat	
Toluene 108-88-3	LD50	5.580 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Epoxy-cyclohexylethyltri-methoxysilane 3388-04-3	LD50	6.700 mg/kg	rabbit	
Toluene 108-88-3	LD50	> 5.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Toluene 108-88-3	LC50	28,1 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Toluene 108-88-3	irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Toluene 108-88-3	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
t- Butylcyclohexylpercarbon ate 15520-11-3	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Epoxy-cyclohexylethyltri methoxysilane 3388-04-3	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Toluene 108-88-3	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Toluene 108-88-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Toluene 108-88-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Toluene 108-88-3	NOAEL 625 mg/kg	oral: gavage	13 weeks daily, 5 days/ week	rat	EU Method B.26 (Sub- Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Toluene 108-88-3	0,57 mm ² /s	40 °C	not specified	

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Epoxyhexahydroxyethyltrimethoxysilane 3388-04-3	LC50	42,3 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Toluene 108-88-3	NOEC	3,2 mg/l	28 d	Cyprinodon variegatus	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Toluene 108-88-3	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
t-Butylcyclohexylpercarbonate 15520-11-3	EC50		48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Epoxyhexahydroxyethyltrimethoxysilane 3388-04-3	EC50	58 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Toluene 108-88-3	EC50	11,5 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Epoxyhexahydroxyethyltrimethoxysilane 3388-04-3	NOEC	16 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Toluene 108-88-3	NOEC	0,74 mg/l	7 d	Ceriodaphnia dubia	other guideline:

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
t-Butylcyclohexylpercarbonate 15520-11-3	EC50		72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
t-Butylcyclohexylpercarbonate 15520-11-3	NOEC		72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Epoxy cyclohexylethyltrimetho xysilane 3388-04-3	NOEC	6 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Epoxy cyclohexylethyltrimetho xysilane 3388-04-3	EC50	90 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Toluene 108-88-3	IC50	12 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Epoxy cyclohexylethyltrimetho xysilane 3388-04-3	EC 50	> 100 mg/l	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Toluene 108-88-3	NOEC	29 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
t-Butylcyclohexylpercarbonate 15520-11-3	not readily biodegradable.	aerobic	3 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Epoxy cyclohexylethyltrimetho xysilane 3388-04-3		aerobic	28 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Toluene 108-88-3	readily biodegradable	aerobic	80 %	20 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Toluene 108-88-3	90	3 d		Leuciscus idus melanotus	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
t-Butylcyclohexylpercarbonate 15520-11-3	8,34		QSAR (Quantitative Structure Activity Relationship)
Epoxy-cyclohexylethyltrimethoxysilane 3388-04-3	4,1	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Toluene 108-88-3	2,73	20 °C	EU Method A.8 (Partition Coefficient)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
t-Butylcyclohexylpercarbonate 15520-11-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Toluene 108-88-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

- 14.1. UN number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H225 Highly flammable liquid and vapor.
- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.