

Revision Number: 007.1 Issue date: 12/06/2019

# PRODUCT AND COMPANY IDENTIFICATION

LOCTITE ECCOBOND LUX AA50T **Product name:** IDH number: 1200659

known as Ablelux AA50T (4.5g),

Product type/use: Adhesive Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887 Internet: w ww.henkelna.com

This product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal. Please contact Henkel Product Safety & Regulatory Affairs for further information.

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE CANCER.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	1B



### **Precautionary Statements**

Obtain special instructions before use. Do not handle until all safety precautions have been Prevention:

read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allow ed out of the workplace. Wear

protective gloves, clothing, eye and face protection.

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several Response:

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Store locked up. Storage:

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

IDH number: 1200659 Product name: LOCTITE ECCOBOND LUX AA50T known as Ablelux AA50T (4.5g), Page 1 of 7

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Formaldehyde polymer w ith 1,1'oxybis[benzene],2-methyl-2-propenoate]		30 - 60	
Polyglycol dimethacrylate	109-16-0	5 - 10	
DI-bornane-2,3-dione	10373-78-1	0.1 - 1	
2-dimethylaminoethyl methacrylate	2867-47-2	0.1 - 1	
Tert-butyl perbenzoate	614-45-9	0.1 - 1	
Paraformaldehyde	30525-89-4	0.1 - 1	•
methacrylic acid	79-41-4	0.1 - 1	

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention.

Symptoms: See Section 11.

IDH number: 1200659

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products: Oxides of carbon, oxides of nitrogen, irritating organic vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sew er or waterways.

Product name: LOCTITE ECCOBOND LUX AA50T known as Ablelux AA50T (4.5g),

Page 2 of 7

Clean-up methods: Remove all sources of ignition. Ensure adequate ventilation. Isolate area.

Keep unnecessary personnel away. Soak up w ith inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, saw dust). Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls /

Personal Protection" prior to clean up.

### 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Keep away from heat, spark and flame.

Refer to Section 8.

Storage: For safe storage, store between -5 °C (23°F) and 5 °C (41°F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Formaldehyde polymer with 1,1'oxybis[benzene],2-methyl-2-propenoate]	None	None	None	None
Polyglycol dimethacrylate	None	None	None	None
DI-bornane-2,3-dione	None	None	None	None
2-dimethylaminoethyl methacrylate	None	None	None	None
Tert-butyl perbenzoate	None	None	None	None
Paraformaldehyde	None	None	None	None
methacrylic acid	20 ppm TWA	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

show ers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid, Paste Color: Off white Odor: Slight Odor threshold: Not available. pH: Not available. Vapor pressure: Not applicable Boiling point/range: Not applicable Melting point/range: Not available. Specific gravity: 0.83 (Water = 1)Vapor density: Not available. > 93 °C (> 199.4 °F) Flash point: Flam mable/Explosive limits - low er: Not available. Flam mable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flam mability: Not applicable

IDH number: 1200659 Product name: LOCTITE ECCOBOND LUX AA50T known as Ablelux AA50T (4.5g),

Page 3 of 7

Evaporation rate: Not available. Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. < 1 % **VOC** content:

Viscosity: Not available. Decomposition temperature: Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

IDH number: 1200659

Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents. Strong reducing agents. Strong acids and strong bases.

Reactivity: Not available.

Conditions to avoid: High temperatures. Exposure to sunlight. UV light. Store away from incompatible materials.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Product name: LOCTITE ECCOBOND LUX AA50T known as Ablelux AA50T (4.5g),

Page 4 of 7

## Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation.

Causes skin irritation. May cause allergic skin reaction. Skin contact:

Eye contact: Causes serious eye irritation.

Ingestion: May cause gastrointestinal tract irritation if sw allowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Formaldehyde polymer w ith 1,1'oxybis[benzene],2-methyl-2-propenoate]	None	No Data
Polyglycol dimethacrylate	None	Irritant, Allergen
DI-bornane-2,3-dione	None	Allergen, Irritant
2-dimethylaminoethyl methacrylate	Oral LD50 (Rat) = 1.55 g/kg	No Data
Tert-butyl perbenzoate	None	Central nervous system, Irritant, Mutagen
Paraformaldehyde	Oral LD50 (Rat) = 800 mg/kg Oral LD50 (Rat) = 800 mg/kg	Allergen, Behavioral, Central nervous system, Irritant, Liver, Metabolic, Mutagen, Reproductive, Respiratory, Some evidence of carcinogenicity
methacrylic acid	Oral LD50 (Mouse) = 1,332 mg/kg Oral LD50 (Mouse) = 1,600 mg/kg Oral LD50 (Mouse) = 1,250 mg/kg Oral LD50 (Rabbit) = 1,200 mg/kg Oral LD50 (Rat) = 1,060 mg/kg Oral LD50 (Rat) = 2,224 mg/kg Dermal LD50 (Rabbit) = 500 mg/kg	Corrosive, Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Formaldehyde polymer with			
1,1'oxybis[benzene],2-methyl-2- propenoate]	No	No	No
Polyglycol dimethacrylate	No	No	No
DI-bornane-2,3-dione	No	No	No
2-dimethylaminoethyl methacrylate	No	No	No
Tert-butyl perbenzoate	No	No	No
Paraformaldehyde	No	No	No
methacrylic acid	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Follow all local, state, federal and provincial regulations for disposal. Recommended method of disposal:

Hazardous waste number: Not a RCRA hazardous waste.

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

IDH number: 1200659

Product name: LOCTITE ECCOBOND LUX AA50T known as Ablelux AA50T (4.5g),

Page 5 of 7

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

### International Air Transportation (ICAO/IATA)

Not regulated Proper shipping name:

Hazard class or division: None Identification number: None Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 6 Risk Management Rules This product is not and cannot be distributed in commerce (as defined in TSCA section

3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal. Please contact Henkel Product Safety & Regulatory Affairs for further

information.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health CERCLA/SARA Section 313: None above reporting de minimis.

Tert-butyl perbenzoate (CAS# 614-45-9) 100 lbs. (45.4 kg) **CERCLA Reportable quantity:** 

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 1200659

California Proposition 65:

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: Review ed SDS. Reissued with new date.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 12/06/2019

Product name: LOCTITE ECCOBOND LUX AA50T known as Ablelux AA50T (4.5g),

Page 6 of 7

**DISCL AIM ER:** The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising fromsale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirmthat the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 1200659