# Safety Data Sheet



Revision Number: 003.0 Issue date: 09/15/2020

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EDAG 965SS E&C known as IDH number: 1238736

**ELECTRODAG 965 SS 1 KG** 

Product type/use: PTF ink

Restriction of Use: None identified Region: United States

Company address:Contact information:Henkel CorporationTelephone: +1 (860) 571-5100

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (tollfree) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (tollfree) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

Ε	EMERGENCY OVERVIEW		
	WARNING:	CAUSES SKIN IRRITATION.	
		CAUSES SERIOUS EYE IRRITATION.	

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

# PICTOGRAM(S)



#### **Precautionary Statements**

IDH number: 1238736

Prevention: Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face

protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Diethylene glycol monoethyl ether acetate	112-15-2	60 - 80
Graphite	7782-42-5	10 - 30
Carbon black - Nano	1333-86-4	5 - 10
Quartz (SiO2), <1% respirable	14808-60-7	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

Product name: LOCTITE EDAG 965SS E&C known as ELECTRODAG 965 SS 1 KG

Page 1 of 5

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Get medical attention. Wash clothing

before reuse. Thoroughly clean shoes before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

**Hazardous combustion products:** Oxides of carbon. Oxides of sulfur. Toxic fumes. Irritating vapors.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sew er or waterways.

Clean-up methods: Evacuate and ventilate spill area; dike spill to prevent entry into w ater system;

w ear full protective equipment during clean-up. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up w ith inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, saw dust). Scrape

up spilled material and place in a closed container for disposal.

### 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed.

**Storage:** For safe storage, store at or below -30 °C (-22°F)

IDH number: 1238736

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Keep away from heat, spark and flame. Protect from

direct sunlight.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Diethylene glycol monoethyl ether acetate	None	None	None	None
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Carbon black - Nano	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL	None	None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

show ers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:BlackOdor:SolventOdor threshold:Not available.pH:Not available.Vapor pressure:Not available.

Boiling point/range: 217 °C (422.6 °F)no method

Melting point/ range:Not available.Specific gravity:1.1Vapor density:Not available.

Flash point: 110 °C (230°F) no method

Flam m able/Explosive limits - lower:
Flam m able/Explosive limits - upper:
Autoignition temperature:
Flam m ability:
Flam m a

VOC content: 62

IDH number: 1238736

**Viscosity:** 15,000 - 50,000 mPa.s

**Decomposition temperature:** Not available.

## 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

**Hazardous reactions:** None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Oxides of sulfur. Toxic fumes. Irritating vapors.

**Incompatible materials:** Strong oxidizing agents. Strong acids and strong bases.

Reactivity: Not available.

**Conditions to avoid:** Keep aw ay from heat, ignition sources and incompatible materials. Protect from direct sunlight.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

**Inhalation:** May cause respiratory tract irritation.

**Skin contact:** Causes skin irritation.

**Eye contact:** Causes serious eye irritation. Redness. Tearing.

Ingestion: May cause gastrointestinal tract irritation if swallowed. This product contains nanoparticles. The

particle size-related health effects of nanoparticles have not been fully investigated.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Diethylene glycol monoethyl ether acetate	Oral LD50 (Rabbit) = 4.4 g/kg Oral LD50 (Rat) = 11 g/kg	Central nervous system, Irritant, Kidney
Graphite	Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3	Lung
Carbon black - Nano	Oral LD50 (Rat) = > 8,000 mg/kg	No Data
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Diethylene glycol monoethyl ether acetate	No	No	No
Graphite	No	No	No
Carbon black - Nano	No	Group 2B	No
Quartz (SiO2), <1% respirable	Know n To Be Human Carcinogen.	Group 1	Yes

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None

Identification number: None
Packing group: None

IDH number: 1238736 Product name: LOCTITE EDAG 965SS E&C known as ELECTRODAG 965 SS 1 KG

Page 4 of 5

#### International Air Transportation (ICAO/IATA)

Not regulated Proper shipping name: Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Propershipping name: Not regulated Hazard class or division: None Identification number: None None Packing group:

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

All components are listed as active or are exempt from listing on the Toxic Substances TSCA 8 (b) Inventory Status:

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Diethylene glycol monoethyl ether acetate (CAS# 112-15-2).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

IDH number: 1238736

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,11,15

Prepared by: Rena Petrides, Regulatory Affairs Specialist

Issue date: 09/15/2020

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirmthat the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

Product name: LOCTITE EDAG 965SS E&C known as ELECTRODAG 965 SS 1 KG