

# LINQTAPE PIT2S-T-RL

2-mil Polyimide Tape | Thin 1mil Silicone Adhesive with Release Liner

- · 2mil Polyimide Film
- 1mil Silicone Adhesive
- >11000 Volts

**LINQTAPE™ PIT2S-T-RL** is a 2-mil thick polyimide film with a thin 1mil silicone pressure adhesive. This adds up to a total thickness of only 3 mil (76.2µm); something that ensures excellent adhesion and mechanical strength at high temperatures. It comes with a clear PET release liner.

LINQTAPE™ PIT2S-T-RL tapes are high performance, temperature-resistant Polyimide tapes that use a polyimide film as a backing film. This backing film is the generic version of DuPont's Kapton HN film and is thin at 2mil (50.8µm) yet is just as flame retardant as its thicker counterparts. Laminated to this is a 1mil (25.4µm) thick pressure-sensitive silicone adhesive making the total thickness of the polyimide film plus adhesive only 3mil (76.2µm) thick. PIT2S-T-RL remains both electrically and mechanically stable across temperatures ranging from -269°C to 400°C (-452°F to 752°F).

Property	Value	Method
Film Thickness	2 mil	ASTM D-3652
Silicone Thickness	1 mil	ASTM D-3652
Total Thickness	3mil	ASTM D-3652
Release liner	Yes	-
Tensile strength	50 lb/in	ASTM D-3759
Elongation	60%	ASTM D-3759
Adhesion to Steel	12.5 Oz/in	ASTM D-3330
Breakdown Voltage	11000 Volts	ASTM D-149
Temperature resistance	260°C	-

## Storage and Handling

Shelf life is 2 years at room temperature in a cool and dry place. Do not put in direct sunlight. No special handling is required.

#### **Europe**

Industrieweg 15E, 1566JN Assendelft The Netherlands

Phone: +31 (20) 893 2224 Email: info@capling.com

## **North America**

957 Snowshoe Crescent Orléans ON, K1C 2Y3 Canada Phone: +1 (613) 482-2215

Email: info@capling.com



## **United States**

847 Sumpter Road #5155 Detroit, MI 48111 United states +1 (313) 558-8243 Email: info@capling.com

#### Asia

Minle Garden, Baoan dst Shenzhen City - 51831

Phone: +861368608 1428 Email: info@capling.com