Revision Date: 12/23/2019 Page 1 of 10

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

(1a,b) TRADE NAME(s)

Aculon® NanoProof® 2.1

1.2 Relevant identified uses of the substance or mixture and uses advised against

[10] CHEMICAL FAMILY/
APPLICATION/ RESTRICTIONS

Chemical Mixture
Hydrocarbon Coating Solution

1.3 Details of the supplier of the safety data sheet



10110 Sorrento Valley Road, San Diego, CA 92121 phone 858-350-9474 fax 858-350-9422

Email: <u>support@aculon.com</u> www.aculon.com 1.4 Emergency telephone number

Emergency Telephone Number [15]

CHEMTEL CHEMICAL

DOMESTIC NORTH AMERICA: 1-800-255-3924

INTERNATIONAL CALLERS OUTSIDE THE US

TERRITORIES AND CANADA: +1-813-248-0585

Revision Date: 12/23/2019

SECTION 2: Hazards identification

Note: The hazards shown on this SDS are for the bulk chemistry and are provided for application/processing safety information. The final coating once dry is not hazardous per 29 CFR 1910 (OSHA HCS)

[24] GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Classification according to EU Directives 67/548/EEC or 1999/45/EC

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225

Skin irritation (Category 2), H315

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Aspiration hazard (Category 1), H304

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

2.2 Label elements Labelling according Regulation (EC) No 1272/2008

LABELING ELEMENTS, Hazard, and Precautionary Statements

Revision Date: 12/23/2019 Page 2 of 10









Signal word: Danger Pictogram(s):

Hazard statement(s):

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P391 Collect spillage.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

^{|20|}HAZARDS NOT OTHERWISE CLASSIFIED: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

[2D]INGREDIENTS OF UNKNOWN ACUTE TOXICITY >/= 1%: none

SECTION 3: Composition/information on ingredients

Hazardous ingredients according to Regulation (EC) No 1272/2008 and 29 CFR 1910 (OSHA HCS)

Revision Date: 12/23/2019 Page 3 of 10

Component	Classification	Concentration	
Methylcyclohexane			
CAS-No. 108-87-2 EC-No.203-624-3 Index-No.601-018-00-1	Flam. Liq. 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Acute 1; Aquatic Chronic 1; H225, H304, H315, H336, H410	82 - 86%	
Proprietary Polymer - not an OSHA Hazardous Material			
CAS-No. n/a EC-No. n/a Index-No. n/a	n/a	14-18%	

^{*} The specific chemical identity and/or percentage of this material has been withheld as a trade secret.

SECTION 4: First aid measures

4.1 Description of f	irst aid measures
General advice	Consult a physician. Show this safety data sheet to the doctor in attendance.
[4a]INHALATION	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a
	physician.
[4a]SKIN CONTACT	Wash off with soap and plenty of water. Consult a physician.
[4a] EYE CONTACT	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
[4a]INGESTION	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with
	water. Consult a physician.
[4b]MOST	The most important known symptoms and effects are described in the labelling (see section 2) and/or
IMPORTANT	in section 11
SYMPTOMS &	
EFFECTS	
[4c]INDICATION OF	no data available
ANY IMMEDIATE	
MEDICAL	
ATTENTION AND	
SPECIAL	
TREATMENT	
NEEDED	

SECTION 5: Firefighting measures

^{[5a] 5.1} Extinguishing Media/SUITABLE/	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
UNSUITABLE EXTINGUISHING	

Revision Date: 12/23/2019 Page 4 of 10

MEDIA	
[5b] 5.2 SPECIFIC	Burning may form Carbon oxides. Use water spray to cool unopened containers.
HAZARDS ARISING	
FROM THE	
SUBSTANCE OR	
MIXTURE(IE	
HAZARDOUS	
COMBUSTION	
PRODUCTS)	
[5c] 5.3	Wear self contained breathing apparatus for fire fighting if necessary.
ADVICE FOR	
FIREFIGHTERS/	
PRECAUTIONS /	
SPECIAL	
PROTECTIVE	
EQUIPMENT	
5.4 FURTHER	Use water spray to cool unopened containers.
INFORMATION	

SECTION 6: Accidental release measures

[6a] 6.1 PERSONAL	Use personal protective equipment. Avoid breathing vapours. Ensure adequate ventilation.
PRECAUTIONS,	Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations.
PPE, EMERGENCY	Vapours can accumulate in low areas.
PROCEDURES	For personal protection see section 8.
6.2 Environmental	Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
precautions	
[6a] 6.3 METHODS &	Contain spillage, wipe up any liquid and place in container for disposal according to local
MATERIALS FOR	regulations (see section 13).
CONTAINMENT &	
CLEANING UP	
^{6.4} REFERENCE TO	For disposal see section 13.
OTHER SECTIONS	

SECTION 7: Handling and storage

[7a] 7.1 PRECAUTIONS	Avoid contact with skin and eyes. Avoid inhalation of vapour. Keep away from sources of ignition -
FOR SAFE	No smoking. Take measures to prevent the buildup of electrostatic charge.
HANDLING	For precautions see section 2.2.
[7b]7.2 CONDITIONS	Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers
FOR SAFE	which are opened must be used immediately before they dry out.
STORAGE,	
INCLUDING ANY	
INCOMPATIBILITIES	
7.3 SPECIFIC END	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated
USES	

SECTION 8: Exposure controls/personal protection

8.1 CONTROL PARAMETERS: COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

Revision Date: 12/23/2019

Page 5 of 10

[8a] COMPONENT	CAS#	PEL/ TWA/ STEL	CONTROL PARAMETERS	BASIS (ACGIH, OSHA ETC)
Methylcyclohexane	108-87-2	TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV) Remarks: Central Nervous system impairment Upper Respiratory Tract irritation Liver damage Kidney damage
		TWA	400 ppm 1600 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	500 ppm 2000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	400 ppm 1,600 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	400 ppm	USA. ACGIH Threshold Limit Values

(TLV)

Liver damage Kidney damage

Central Nervous System impairment Upper Respiratory Tract irritation

[8b] 8.2 EXPOSURE	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks
CONTROLS/	and at the end of workday.
VENTILATION /	
ENGINEERING	
CONTROLS	
PERSONAL PROTEC	TIVE EQUIPMENT
[8c] RESPIRATORY	Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator
PROTECTION	with multi purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup
	to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air
	respirator. Use respirators and components tested and approved under appropriate government
	standards such as NIOSH (US) or CEN (EU).
[8c]SKIN PROTECTION	Handle with gloves. Dispose of contaminated gloves after use in accordance with applicable laws
	and good laboratory practices.
	Wash and dry hands.
	Full contact
	Material: Nitrile rubber
	Minimum layer thickness: 0.4 mm
	Break through time: 480 min
	Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)
	Splash contact
	Material: Nitrile rubber
	Minimum layer thickness: 0.11 mm
	Break through time: 35 min

Revision Date: 12/23/2019 Page 6 of 10

	Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)
	data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de,
	test method:
	EN374
	If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.
[8c]EYE PROTECTION	Safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
[8c]CLOTHING/BODY	Wear impervious clothing. The type of protective equipment must be selected according to the
	concentration and amount of the dangerous substance at the specific workplace.
CONTROL OF	Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
ENVIRONMENTAL	
EXPOSURE	

SECTION 9: Physical and chemical properties

[9a]Appearance (physical state, color, etc.	Thick Liquid, Clear Colorless	[9j]Upper/lower flammability or explosive limits:	Lower: 1.1% UEL: 6.7%
[9b] Odor	no data available	[9k]Vapor pressure	110.9 hPa (83.2 mmHg) at 37.7 °C (99.9 °F) 49.3 hPa (37.0 mmHg) at 20.0 °C (68.0 °F)
[9c]Odor threshold	no data available	[9ɪ]Vapor density	no data available
[9d] PH	no data available	[9m]Relative Density	0.77 g/cm3 at 25 °C
[9e]]Melting point/freezing point	-126 °C (-195 °F) - lit	[9n]Solubility (in H ₂ O)	no data available
թղInitial boiling point and boiling range	101 °C (214 °F) - lit.	[90]Partition coefficient: n-octanol/water	log Pow: 3.44
[9g]Flash point	-4.0 °C (24.8 °F) - closed cup	[9p]Auto-ignition temperature	283.0 °C (541.4 °F)
[9h]Evaporation rate	no data available	թգյDecomposition temperature	no data available
เตเรา [ตเรา [ตเรา [ตรา [ตรา [ตรา [ตรา [ตรา [ตรา [ตรา [ต	no data available	[9r]Viscosity	no data available
		[9s]Explosive Properties	no data available
		[9t]Oxidizing Properties	no data available

9.2 Other safety information: No data available

SECTION 10: Stability and reactivity

[10a 10.1] REACTIVITY	no data available		
[10b 10.2] CHEMICAL	stable under recommended storage conditions		
STABILITY			
[10c 10.3] POSSIBILITIES	/apours may form explosive mixture with air.		
OF HAZARDOUS			

Revision Date: 12/23/2019 Page 7 of 10

REACTIONS	
[10d 10.4] CONDITIONS TO	Ignition sources, excess heat, incompatible materials
AVOID	
[10e 10.5] INCOMPATIBLE	Strong oxidizing agents,
MATERIALS	
[10f 10.6] HAZARDOUS	Other decomposition products - no data available
DECOMPOSITION	In the event of fire: see section 5
PRODUCTS	

SECTION 11: Toxicological information

[11a] LIKELY ROUTES			
OF EXPOSURE			
OF EXPOSURE	INHALATION: is not expected if proper ventilation or personal protective equipment is used while		
	working with this product		
	INGESTION: Ingestion is not expected if proper industrial hygiene practices are followed, including		
	no eating, drinking, or smoking while working with chemicals		
	SKIN: is not expected if proper personal protective equipment (gloves and protective clothing) is		
	used while working with this product		
	EYE CONTACT: is not expected if proper personal protective equipment (safety glasses or		
	goggles) is used while working with this product		
	goggies) is used write working with this product		
[11b] SYMPTOMS	INHALATION: May be fatal if swallowed and enters airways.		
RELATED TO	INGESTION: May be fatal if swallowed and enters airways.		
PHYSICAL,	SKIN: May result in mild eye irritation		
CHEMICAL & TOXIC	EYE CONTACT: no data available		
CHARACTERISTICS			
[11d] DELAYED /	Reproductive toxicity: Rat - male and female - Oral No toxicity to reproduction		
IMMEDIATE	Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.		
EFFECTS,			
	Specific target organ toxicity - repeated exposure: no data available		
	Aspiration hazard: May be fatal if swallowed and enters airways.		
FROM			
SHORT/LONG			
TERM EXPOSURE			
[11D] NUMERICAL	ACUTE TOXICITY ESTIMATES: none known		
MEASURES OF			
TOXICITY	Acute toxicity		
	No data available		
	Inhalation: No data available		
	Dermal: No data available		
	No data available		
	INO data available		
	OKAN GODDOGONADDITATION		
	SKIN CORROSION/IRRITATION		
	No data available		
	Serious eye damage/eye irritation		
	Eyes - Rabbit		
	Result: No eye irritation		
	(OECD Test Guideline 405)		
	Respiratory or skin sensitization		
	No data available		

Revision Date: 12/23/2019 Page 8 of 10

	Germ cell mutagenicity Did not show mutagenic effects in animal experiments.	
	Chromosome aberration test in vitro	
	Chinese hamster lung cells Result: negative	
	Ames test	
	Salmonella typhim	
	No component of this product present at levels greater than or equal to 0.1% is identified as	
CARCINOGENICITY	probable, possible or confirmed human carcinogen by IARC, NTP, or OSHA	
	Repeated dose	
	toxicity	
	Rat - male and female - Oral - NOAEL : 250 mg/kg	
	Rat - male and female - Inhalation - NOAEL : 1.6 mg/l	
	RTECS: GV6125000	
	prolonged or repeated exposure can cause:, narcosis	

SECTION 12: Ecological information

[12a 12.1] ECOTOXICITY	Toxicity to fish semi-static test LC50 - Oryzias latipes - 2.07 mg/l - 96 h
	(OECD Test Guideline 203)
	Toxicity to daphnia and
	other aquatic
	invertebrates
	semi-static test EC50 - Daphnia magna (Water flea) - 0.326 mg/l - 48 h
	Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata (green algae) - 0.134 mg/l -
	72 h
[12b 12.2]PERSISTENCE	This product is not biodegradable
AND	
DEGRADABILITY	
[12c 12.3]	No data available
BIOACCUMULATIVE	
POTENTIAL	
[12d 12.4] MOBILITY IN	No data available
SOIL	
12.5	PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
RESULTS OF PBT	
AND vPvB	
ASSESSMENT	
[12e 12.6] OTHER	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
ADVERSE EFFECTS	Very toxic to aquatic life with long lasting effects.
(OZONE LAYER	
ETC.)	

SECTION 13: Disposal considerations

Revision Date: 12/23/2019 Page 9 of 10

[13]Contact a licensed professional waste disposal service.	
Contaminated Packaging Disposal: Contact a licensed professional waste disposal service.	

SECTION 14: Transport information

	14.1[a] UN number	14.2[b] UN proper shipping name	14.3[c] Transport hazard class(es)	14.4[d] Packaging group	14.5[e] Environmental hazards
ADR/RID:	UN2296	Methylcyclohexane	3	П	not applicable
IMDG:	UN2296	Methylcyclohexane	3	II	EMS-NO: F-E, S-D Marine Pollutant: yes
IATA:	UN2296	Methylcyclohexane	3	II	not applicable
US DOT	UN2296	Methylcyclohexane	3	II	not applicable
14.6 Special precautions for user	N/A				

[14d] ENVIRONMENTAL	Marine Pollutant: yes	
HAZARDS		
[14f] BULK TRANSPORT	IMDG: UN2296, Methylcyclohexane, 3, II EMS-No: F-E, S-D	
(MARPOL 73/78/IBC CODE)		
[14g]SPECIAL PRECAUTIONS	none known	

SECTION 15: Regulatory information

EU This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.		
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	No data available	
15.2 Chemical Safety Assessment	For this product a chemical safety assessment was not carried out	

|--|

TSCA	The components in this mixture are listed on the US inventory.
OSHA	This document has been prepared in accordance with the SDS requirements

Revision Date: 12/23/2019 Page 10 of 10

	of the OSHA Hazard Communication Standard.
SARA SECTION 302 EXTREMELY	No chemicals in this material are subject to the reporting requirements of
HAZARDOUS SUBSTANCES	SARA Title III, Section 302.
The following components are subject to	This material does not contain any chemical components with known CAS
reporting levels established by SARA	numbers that exceed the threshold (De
Title III, Section 313	Minimis) reporting levels established by SARA Title III, Section 313.
Sara 311/312 Hazards	Fire Hazard, Acute Health Hazard, Chronic Health Hazard
Massachusetts Right To Know	Methylcyclohexane
Components	CAS-No. 108-87-2, Revision Date 1993-04-24
Pennsylvania Right To Know	Methylcyclohexane
Components	CAS-No. 108-87-2, Revision Date 1993-04-24
New Jersey Right To Know Components	Methylcyclohexane
	CAS-No. 108-87-2, Revision Date 1993-04-24
California Prop. 65 Components	This product does not contain any chemicals known to State of California to
	cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Revision Date: 12/23/2019 Updated Address under Section 1

01/25/2019 Updated "Note" under section 2

06/14/2018 Updated Emergency Contact and Trademarks

03/13/18

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute Acute aquatic toxicity

Aguatic Chronic Chronic aguatic toxicity

Asp. Tox. Aspiration hazard

Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Skin Irrit. Skin irritation

INFORMATION CONTAINED IN THIS SAFETY DATA SHEET IS FOR USE BY TECHNICALLY QUALIFIED PERSONNEL AT THEIR DISCRETION AND RISK. ALL STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON TESTS AND DATA WHICH WE BELIEVE TO BE RELIABLE, BUT THE ACCURACY OR COMPLETENESS THEREOF IS NOT GUARANTEED AND NO WARRANT OF ANY KIND IS MADE WITH RESPECT THERETO. SINCE THE COMPANY SHALL HAVE NO CONTROL OF THE USE OF THE PRODUCT DESCRIBED HEREIN, THE COMPANY ASSUMES NO LIABILITY OF LOSS OR DAMAGE INCURRED FROM THE PROPER OR IMPROPER USE OF SUCH PRODUCT.

DISCLAIMER

This material must be handled by/under direct supervision of technically qualified persons. Not for drug, household or other uses.