

Revision Number: 004.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type/use:

Restriction of Use:

Company address:

Henkel Corporation

Rocky Hill, Connecticut 06067

One Henkel Way

LOCTITE ECCOBOND FP4655 known as 30CC FP4655 LWSTRESS EN/CH -40C

Encapsulant

None identified


own IDH number: CH - 1643904

Item number:45250Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

| EMERGENCY OVERVIEW | | | |
|--------------------|---|--|--|
| DANGER: | MAY CAUSE AN ALLERGIC SKIN REACTION. | | |
| | CAUSES SERIOUS EYE DAMAGE. | | |
| | MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING | | |
| | DIFFICULTIES IF INHALED. | | |
| | MAY CAUSE RESPIRATORY IRRITATION. | | |
| | MAY DAMAGE FERTILITY OR THE UNBORN CHILD. | | |

| HAZARD CLASS | HAZARD CATEGORY |
|--|-----------------|
| SERIOUS EYE DAMAGE | 1 |
| RESPIRATORY SENSITIZATION | 1 |
| SKIN SENSITIZATION | 1 |
| REPRODUCTIVE TOXICITY | 1B |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE | 3 |



Precautionary Statements

| Prevention: | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors, mist, or spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate ventilation wear respiratory protection. |
|-------------|---|
| Response: | IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. |
| Storage: | Store in a well-ventilated place. Keep container tightly closed. Store locked up. |
| Disposal: | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations. |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

Product name: LOCTITE ECCOBOND FP4655 known as 30CC FP4655 LWSTRESS EN/CH -40C Page 1 of 6

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* | |
|-----------------------------------|-------------|-------------|--|
| Silica, vitreous | 60676-86-0 | 60 - 90 | |
| Silicon dioxide | 7631-86-9 | 5 - 10 | |
| hexahydromethylphthalic anhydride | 25550-51-0 | 5 - 10 | |
| Epoxy resin | Proprietary | 1 - 5 | |
| Epoxy resin | Proprietary | 1 - 5 | |
| Cycloaliphatic epoxy | Proprietary | 0.1 - 1 | |
| Substituted phthalic anhydride | 34090-76-1 | 0.1 - 1 | |
| Carbon black | 1333-86-4 | 0.1 - 1 | |
| 1-Benzyl-2-methyl-1H-imidazole | 13750-62-4 | 0.1 - 1 | |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

| 4. | FIRST AID MEASURES |
|------------------------------------|--|
| Inhalation: | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. |
| Skin contact: | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. |
| Eye contact: | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention. |
| Ingestion: | Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention. |
| Symptoms: | See Section 11. |
| 5. FI | RE FIGHTING MEASURES |
| Extinguishing media: | Water spray (fog), foam, dry chemical or carbon dioxide. |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. |
| Unusual fire or explosion hazards: | Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. |
| Hazardous combustion products: | Oxides of carbon. Toxic and irritating vapors. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Clean-up methods:

Do not allow product to enter sewer or waterways.

Remove all sources of ignition. Ensure adequate ventilation. Isolate area. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|---|--|--|-----------|-------------------------------------|
| Silica, vitreous | 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. | 20 MPPCF TWA 0.8 mg/m3 TWA 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. | None | None |
| Silicon dioxide | 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. 6 mg/m3 TWA | 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. | None | 3 mg/m3 TWA Respirable fraction. |
| hexahydromethylphthalic anhydride | None | None | None | None |
| Epoxy resin | None | None | None | None |
| Epoxy resin | None | None | None | None |
| Cycloaliphatic epoxy | None | None | None | None |
| Substituted phthalic anhydride | 0.0003 ppm STEL 0.00007 ppm TWA 0.7 mg/100 cm2 TLV- SL (SKIN) (Dermal sensitization) (Respiratory sensitization) | None | None | None |
| Carbon black | 3 mg/m3 TWA Inhalable fraction. | 3.5 mg/m3 PEL 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. | None | None |
| 1-Benzyl-2-methyl-1H-imidazole | None | None | None | None |
| Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. | | | | |
| Respiratory protection: | | NOSH approved air-purit shed exposure limits exis | | ential to exceed |
| Eye/face protection: | protection:Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available. | | | |
| Skin protection: | Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. | | | |
| IDH number: 1643904 Product name: LOCTITE ECCOBOND FP4655 known as 30CC FP4655 LWSTRESS EN/CH -40C Page 3 of 6 | | | | |

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

| Stability: | Stable under normal conditions of storage and use. | |
|--------------------------------------|--|--|
| Hazardous reactions: | None under normal processing. | |
| Hazardous decomposition products: | Oxides of carbon. Irritating vapors. | |
| Incompatible materials: | Strong oxidizing agents. Strong acids and strong bases. Water | |
| Reactivity: | Not available. | |
| Conditions to avoid: | High temperatures. Store away from incompatible materials. Heat, flames, sparks and other sources of ignition. | |
| 11. TOXICOLOGICAL INFORMATION | | |

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:

May cause respiratory tract irritation. May cause allergic respiratory reaction. Coughing. Wheezing. Shortness of breath. Skin contact: May cause skin irritation. May cause allergic skin reaction. Eye contact: Causes serious eye damage. Ingestion: May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|-----------------------------------|--|--|
| Silica, vitreous | None | Nuisance dust |
| Silicon dioxide | Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 2.08 mg/l Inhalation LC50 (Rat, 4 h) = > 0.69 mg/l | Nuisance dust |
| hexahydromethylphthalic anhydride | None | Allergen, Respiratory, Irritant |
| Epoxy resin | None | Allergen, Irritant |
| Epoxy resin | None | Allergen, Irritant |
| Cycloaliphatic epoxy | None | Allergen, Irritant |
| Substituted phthalic anhydride | None | Irritant, Allergen, Respiratory |
| Carbon black | Oral LD50 (Rat) = > 8,000 mg/kg | Respiratory, Some evidence of carcinogenicity |
| 1-Benzyl-2-methyl-1H-imidazole | None | Allergen, Reproductive |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|-----------------------------------|----------------|-----------------|---|
| Silica, vitreous | No | No | No |
| Silicon dioxide | No | No | No |
| hexahydromethylphthalic anhydride | No | No | No |
| Epoxy resin | No | No | No |
| Epoxy resin | No | No | No |
| Cycloaliphatic epoxy | No | No | No |
| Substituted phthalic anhydride | No | No | No |
| Carbon black | No | Group 2B | No |
| 1-Benzyl-2-methyl-1H-imidazole | No | No | No |

ECOLOGICAL INFORMATION 12.

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

TRANSPORT INFORMATION 14.

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

| Proper shipping name: | No |
|---------------------------|----|
| Hazard class or division: | No |
| Identification number: | No |
| Packing group: | No |

ot regulated one one lone

International Air Transportation (ICAO/IATA)

| Proper shipping name: | Not regulated |
|---------------------------|---------------|
| Hazard class or division: | None |
| Identification number: | None |
| Packing group: | None |

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

| TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification: | All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. None above reporting de minimis |
|--|---|
| CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: | None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis. |
| California Proposition 65: | This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. |
| Canada Regulatory Information | |
| CEPA DSL/NDSL Status: | Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details. |

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11,13,16

Prepared by: Product Safety and Regulatory Affairs

Issue date: 04/25/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.