



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 21

LOCTITE EDAG 452SS E&C known as ELECTRODAG 452 SS 1 KG

SDS No. : 326077

V002.0

Revision: 13.04.2023

printing date: 19.12.2023

Replaces version from: 21.09.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EDAG 452SS E&C known as ELECTRODAG 452 SS 1 KG

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

UV curable dielectric ink

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ireland

Operations and Research Limited

Tallaght Business Park, Whitestown

24 Dublin

Ireland

Phone: +353 (0353) 1 404 6444

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

00353 14046280

National Poisons Information Centre: Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week)

Healthcare Professionals: +353 (1) 809 2566 (24-hour service)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

**Carcinogenicity Category 1B**

**H350 May cause cancer.**

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

**Hazard pictogram:****Contains**

2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate

1,6-Hexanediol diacrylate  
BenzophenoneIsobornyl acrylate  
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate**Signal word:****Danger****Hazard statement:**H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H350 May cause cancer.  
H411 Toxic to aquatic life with long lasting effects.**Precautionary statement:**  
**Prevention**P201 Obtain special instructions before use.  
P273 Avoid release to the environment.  
P261 Avoid breathing vapors.  
P280 Wear protective gloves/protective clothing.**Precautionary statement:**  
**Response**P308+P313 IF exposed or concerned: Get medical advice/attention.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**2.3. Other hazards**

None if used properly.

Care should be taken during the cure of these products by UV radiation to avoid exposure of the skin and especially of the eyes to direct or reflected UV radiation as long term effects could be harmful.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5 265-991-6	25- 50 %	Skin Irrit. 2, Dermal, H315 Eye Irrit. 2, H319 STOT SE 3, Inhalation, H335 Aquatic Chronic 2, H411		
Acrylated urethane oligomer~	25- 50 %	Eye Irrit. 2, H319		
1,6-Hexanediol diacrylate 13048-33-4 235-921-9 01-2119484737-22	1- < 5 %	Aquatic Acute 1, H400 Aquatic Chronic 2, H411 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	M acute = 1	
2,2-Diethoxyacetophenone 6175-45-7 228-220-4	1- < 5 %	Eye Irrit. 2, H319		
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8 246-386-6 01-2120000336-73	0,25- < 2,5 %	Aquatic Chronic 1, H410 Aquatic Acute 1, H400	M acute = 1 M chronic = 1	
Benzophenone 119-61-9 204-337-6 01-2119899704-20	0,1- < 1 %	Aquatic Chronic 3, H412 STOT RE 2, H373 Carc. 1B, H350		
Isobornyl acrylate 5888-33-5 227-561-6 01-2119957862-25	0,25- < 2,5 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5 256-032-2 01-2119484613-34	0,1- < 1 %	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	STOT SE 3; H335; C >= 10 %	

For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

#### Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

#### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

#### Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Ventilation will remove any ozone that may be produced by the ultra violet lamp

**Hygiene measures:**

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in sealed original container.

Store in a dry place.

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

UV curable dielectric ink

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC]		10	Time Weighted Average (TWA):		IR_OEL
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC]		0,8	Time Weighted Average (TWA):		IR_OEL
Polyethylene 9002-88-4 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Polyethylene 9002-88-4 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL

**Occupational Exposure Limits**Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc 14807-96-6 [TALC, RESPIRABLE DUST]		1	Time Weighted Average (TWA):		EH40 WEL
Polyethylene 9002-88-4 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Polyethylene 9002-88-4 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Hexamethylene diacrylate 13048-33-4	aqua (freshwater)		0,007 mg/l				
Hexamethylene diacrylate 13048-33-4	aqua (marine water)		0,001 mg/l				
Hexamethylene diacrylate 13048-33-4	Soil				0,094 mg/kg		
Hexamethylene diacrylate 13048-33-4	sewage treatment plant (STP)		2,7 mg/l				
Hexamethylene diacrylate 13048-33-4	sediment (freshwater)				0,493 mg/kg		
Hexamethylene diacrylate 13048-33-4	sediment (marine water)				0,049 mg/kg		
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	aqua (freshwater)		0,229 mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Freshwater - intermittent		0,184 mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	aqua (marine water)		0,0229 mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	sewage treatment plant (STP)		19,4 mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	sediment (freshwater)				8,87 mg/kg		
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	sediment (marine water)				0,887 mg/kg		
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Soil				1,64 mg/kg		
Benzophenone 119-61-9	aqua (freshwater)		0,02 mg/l				
Benzophenone 119-61-9	aqua (marine water)		0,002 mg/l				
Benzophenone 119-61-9	aqua (intermittent releases)		0,035 mg/l				
Benzophenone 119-61-9	sediment (freshwater)				1,1 mg/kg		
Benzophenone 119-61-9	sediment (marine water)				0,11 mg/kg		
Benzophenone 119-61-9	sewage treatment plant (STP)		3,16 mg/l				
Benzophenone 119-61-9	Soil		0,31 mg/l				
Isobornyl acrylate 5888-33-5	aqua (freshwater)		0,001 mg/l				
Isobornyl acrylate 5888-33-5	aqua (intermittent releases)		0,007 mg/l				
Isobornyl acrylate 5888-33-5	aqua (marine water)		0,0001 mg/l				
Isobornyl acrylate 5888-33-5	sewage treatment plant (STP)		2 mg/l				
Isobornyl acrylate 5888-33-5	sediment (freshwater)				0,145 mg/kg		
Isobornyl acrylate 5888-33-5	sediment (marine water)				0,0145 mg/kg		
Isobornyl acrylate 5888-33-5	Soil				0,0285 mg/kg		
Isobornyl acrylate 5888-33-5	Predator						no potential for bioaccumulation
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	aqua (freshwater)		0,005 mg/l				
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Freshwater - intermittent		0,046 mg/l				
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-	aqua (marine		0 mg/l				

2,1-ethanediyl)] diacrylate 42978-66-5	water)						
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	sewage treatment plant (STP)		10 mg/l				
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	sediment (freshwater)				0,487 mg/kg		
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	sediment (marine water)				0,049 mg/kg		
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Soil				0,095 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hexamethylene diacrylate 13048-33-4	Workers	dermal	Long term exposure - systemic effects		2,77 mg/kg	
Hexamethylene diacrylate 13048-33-4	Workers	inhalation	Long term exposure - systemic effects		24,48 mg/m3	
Hexamethylene diacrylate 13048-33-4	General population	dermal	Long term exposure - systemic effects		1,66 mg/kg	
Hexamethylene diacrylate 13048-33-4	General population	inhalation	Long term exposure - systemic effects		7,24 mg/m3	
Hexamethylene diacrylate 13048-33-4	General population	oral	Long term exposure - systemic effects		2,08 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Workers	inhalation	Long term exposure - systemic effects		2,11 mg/m3	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Workers	dermal	Long term exposure - systemic effects		0,599 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	inhalation	Long term exposure - systemic effects		0,372 mg/m3	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	dermal	Long term exposure - systemic effects		0,214 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	oral	Long term exposure - systemic effects		0,214 mg/kg	
Benzophenone 119-61-9	Workers	inhalation	Long term exposure - systemic effects		0,7 mg/m3	
Benzophenone 119-61-9	Workers	dermal	Long term exposure - systemic effects		0,1 mg/kg	
Benzophenone 119-61-9	General population	inhalation	Long term exposure - systemic effects		0,17 mg/m3	
Benzophenone 119-61-9	General population	dermal	Long term exposure - systemic effects		0,05 mg/kg	
Benzophenone 119-61-9	General population	oral	Long term exposure - systemic effects		0,05 mg/kg	
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - systemic effects		1,39 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Workers	inhalation	Long term exposure - systemic effects		2,35 mg/m3	
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Workers	dermal	Long term exposure - systemic effects		1,7 mg/kg	



**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

Ensure good ventilation/extraction.

UV lamp should be designed, installed and operated in such a way as to eliminate exposure of the skin and eyes to stray radiation

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to &gt; 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to &gt; 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Delivery form	liquid
Colour	green
Odor	None
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	$< 0^{\circ}\text{C}$ ( $< 32^{\circ}\text{F}$ )
Initial boiling point	$240^{\circ}\text{C}$ ( $464^{\circ}\text{F}$ )
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	$> 93^{\circ}\text{C}$ ( $> 199.4^{\circ}\text{F}$ )
Auto-ignition temperature	$> 200^{\circ}\text{C}$ ( $> 392^{\circ}\text{F}$ )
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) ( $20^{\circ}\text{C}$ ( $68^{\circ}\text{F}$ ); )	$> 1.000$ mm <sup>2</sup> /s
Viscosity, dynamic ( )	12.000 cp no method / method unknown
Viscosity, dynamic (; $25^{\circ}\text{C}$ ( $77^{\circ}\text{F}$ ))	9.000 - 17.000 cp Internal Henkel specification
Solubility (qualitative)	Insoluble

(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure (20 °C (68 °F))	< 1 hPa
Density (20 °C (68 °F))	1,27 g/cm <sup>3</sup> None
Density (20 °C (68 °F))	10,3 - 10,7 lb/gal Internal Henkel specification
Relative vapour density: (20 °C)	> 1
Particle characteristics	Not applicable
	Product is a liquid

## 9.2. Other information

Other information not applicable for this product

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reaction with strong oxidants.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

Protect from direct sunlight.

Avoid contact with acids and oxidizing agents.

Heat, flames, sparks and other sources of ignition.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

carbon oxides.

Hydrocarbons

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5	LD50	> 5.000 mg/kg	rat	
1,6-Hexanediol diacrylate 13048-33-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2,2-Diethoxyacetophenone 6175-45-7	LD50	5.660 mg/kg	rat	not specified
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	LD50	> 5.000 mg/kg	rat	not specified
Benzophenone 119-61-9	LD50	2.895 mg/kg	mouse	OECD Guideline 401 (Acute Oral Toxicity)
Isobornyl acrylate 5888-33-5	LD50	4.350 mg/kg	rat	not specified
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)

#### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5	LD50	> 5.000 mg/kg	rabbit	
1,6-Hexanediol diacrylate 13048-33-4	LD50	3.650 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2,2-Diethoxyacetophenone 6175-45-7	LD50	11.300 mg/kg	rat	not specified
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	LD50	> 5.000 mg/kg	rat	not specified
Benzophenone 119-61-9	LD50	3.535 mg/kg	rabbit	not specified
Isobornyl acrylate 5888-33-5	LD50	> 3.000 mg/kg	rabbit	not specified
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

No data available.

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
1,6-Hexanediol diacrylate 13048-33-4	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Benzophenone 119-61-9	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Isobornyl acrylate 5888-33-5	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
1,6-Hexanediol diacrylate 13048-33-4	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Benzophenone 119-61-9	slightly irritating		rabbit	not specified
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	moderately irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
1,6-Hexanediol diacrylate 13048-33-4	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Benzophenone 119-61-9	not sensitising	Draize Test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Benzophenone 119-61-9	not sensitising	Patch-Test	human	Patch Test
Isobornyl acrylate 5888-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

<b>Hazardous substances CAS-No.</b>	<b>Result</b>	<b>Type of study / Route of administration</b>	<b>Metabolic activation / Exposure time</b>	<b>Species</b>	<b>Method</b>
1,6-Hexanediol diacrylate 13048-33-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,6-Hexanediol diacrylate 13048-33-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Benzophenone 119-61-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Benzophenone 119-61-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		not specified
Benzophenone 119-61-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl acrylate 5888-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobornyl acrylate 5888-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl acrylate 5888-33-5	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
(1-methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
(1-methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,6-Hexanediol diacrylate 13048-33-4	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Benzophenone 119-61-9	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
(1-methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity**

No data available.

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
1,6-Hexanediol diacrylate 13048-33-4	NOAEL P 250 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Benzophenone 119-61-9	NOAEL P > 2000 ppm NOAEL F1 450 ppm NOAEL F2 450 ppm	two- generation study	oral: feed	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Isobornyl acrylate 5888-33-5	NOAEL P 100 mg/kg NOAEL F1 100 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
(1-methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	NOAEL P 250 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
1,6-Hexanediol diacrylate 13048-33-4	NOAEL 250 mg/kg	oral: gavage	28 - 52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Benzophenone 119-61-9	NOAEL < 75 mg/kg	oral: feed	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isobornyl acrylate 5888-33-5	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
(1-methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	NOAEL 250 mg/kg	oral: gavage	28 - 52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

**Aspiration hazard:**

No data available.

#### **11.2 Information on other hazards**

not applicable

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5	LC50	9 mg/l	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,6-Hexanediol diacrylate 13048-33-4	LC50	0,38 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,072 mg/l	39 d	Oryzias latipes	OECD Guideline 210 (fish early life stage toxicity test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	LC50	7,2 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzophenone 119-61-9	LC50	15,3 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzophenone 119-61-9	NOEC	5,86 mg/l	7 d	Pimephales promelas	OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
Isobornyl acrylate 5888-33-5	LC50	0,704 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	LC50	> 4,5 - 10 mg/l	96 h	Leuciscus idus	DIN 38412-15

#### Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,6-Hexanediol diacrylate 13048-33-4	EC50	2,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	EC50	26 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Benzophenone 119-61-9	EC50	6,78 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isobornyl acrylate 5888-33-5	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	EC50	88,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
----------------------	-------	-------	---------------	---------	--------



CAS-No.	type				
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,14 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Benzophenone 119-61-9	NOEC	0,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Isobornyl acrylate 5888-33-5	NOEC	0,092 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,6-Hexanediol diacrylate 13048-33-4	EC50	2,33 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,9 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	EC50	0,17 mg/l	72 h	Scenedesmus sp.	OECD Guideline 201 (Alga, Growth Inhibition Test)
Benzophenone 119-61-9	NOEC	1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Benzophenone 119-61-9	EC50	3,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	NOEC	0,405 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	EC50	1,98 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	EC50	28 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

**Toxicity (microorganisms):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,6-Hexanediol diacrylate 13048-33-4	EC20	60 mg/l	30 min	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	EC 50	> 100 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Benzophenone 119-61-9	EC 50	787 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	EC 50	> 10.000 mg/l	30 min		not specified

**12.2. Persistence and degradability**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5		aerobic	0 %	30 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,6-Hexanediol diacrylate 13048-33-4	readily biodegradable	aerobic	69 %	28 d	OECD Guideline 310 (Ready Biodegradability: CO <sub>2</sub> in Sealed Vessels (Headspace Test))
1,6-Hexanediol diacrylate 13048-33-4	inherently biodegradable	aerobic	> 70 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	not readily biodegradable.	aerobic	3 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO <sub>2</sub> Evolution Test)
Benzophenone 119-61-9	readily biodegradable	aerobic	66 - 84 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Isobornyl acrylate 5888-33-5	inherently biodegradable	aerobic	73,9 %	60 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Isobornyl acrylate 5888-33-5	not readily biodegradable.	aerobic	57 %	28 d	OECD Guideline 310 (Ready Biodegradability: CO <sub>2</sub> in Sealed Vessels (Headspace Test))
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	not readily biodegradable.	aerobic	48 %	28 d	EU Method C.4-C (Determination of the "Ready" Biodegradability: Carbon Dioxide Evolution Test)

### 12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Benzophenone 119-61-9	3,4 - 12	56 d		Oryzias latipes	other guideline:
Isobornyl acrylate 5888-33-5	37	56 h	24 °C	Danio rerio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

**12.4. Mobility in soil**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
1,6-Hexanediol diacrylate 13048-33-4	2,81	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	3,42		not specified
Benzophenone 119-61-9	3,18	25 °C	EU Method A.8 (Partition Coefficient)
Isobornyl acrylate 5888-33-5	4,52		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	< 4		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

**12.5. Results of PBT and vPvB assessment**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
1,6-Hexanediol diacrylate 13048-33-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethanone, 2,2-dimethoxy-1,2-diphenyl- 24650-42-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Benzophenone 119-61-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isobornyl acrylate 5888-33-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**12.6. Endocrine disrupting properties**

not applicable

**12.7. Other adverse effects**

No data available.

## SECTION 13: Disposal considerations

**13.1. Waste treatment methods**

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080312

## SECTION 14: Transport information

### 14.1. UN number or ID number

ADR	3082
RID	3082
IMDG	3082
IATA	3082

### 14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclopentyloxyethyl acrylate)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclopentyloxyethyl acrylate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclopentyloxyethyl acrylate)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Dicyclopentyloxyethyl acrylate)

### 14.3. Transport hazard class(es)

ADR	9
RID	9
IMDG	9
IATA	9

### 14.4. Packing group

ADR	III
RID	III
IMDG	III
IATA	III

### 14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

### 14.6. Special precautions for user

ADR	not applicable Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content	
VOC content (2010/75/EC)	< 3 %

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H350 May cause cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2:	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**