

LINQSTAT MVCF-8S10K

Carbon filled polyethylene film



- 8 mil film
- Black color
- $\pm 10,000$ ohms/sq Surface resistivity

LINQSTAT MVCF-8S10K is a black, carbon-filled, electrically conductive polyethylene plastic film designed to provide both physical and static protection. With a surface resistivity below $5 \times 10^4 \Omega/\text{sq}$ it offers medium-level static protection which means it effectively avoids accumulation of electric charge on itself and the products which it protects. Its easy-grounding nature makes it ideal for packaging where electrostatic contamination is a problem.

MVCF-8S10K is useful in applications where the key is to balance cost versus performance. As a medium-level conductive plastic, the carbon-loading is such that it is low-enough to be cost-effective, while being high enough to meet the electrical requirements of military specification MIL-PRF-81705D Type II and MIL-P-82646A.

Specifications

Property	Value	Unit
Color	Black	-
Chemistry Type	Carbon-Loaded PE	-
Film Thickness	203 (8)	um (mil)
Surface Resistivity	± 10000	ohm
Tensile Strength	24.5	mPa
Elongation	>340	%
Melting Temperature	115-130	°C
Thermal Conductivity	0.053	W/(mK)
Density	1	g/cm ³
Specific Gravity	1.05	-

Storage and Handling

Shelf life is 5 years if stored in a dry and cool, well ventilated place at room temperature.

The product is supplied in rolls and it's conductivity is unaffected by humidity and age. The film is heat sealable, flexible, and offers exceptional abrasion resistance.

Europe

Industrieweg 15E,
1566JN Assendelft
The Netherlands
Phone: +31 (20) 893 2224
Email: info@caplinq.com

Canada

80 Sirocco Crescent
Ottawa ON, K2S 2C9
Canada
Phone: +1 (613) 482-2215
Email: info@caplinq.com



North America

36927 Schoolcraft Rd
Livonia, MI 48150
United States
Phone: +1 (313) 558-8243
Email: info@caplinq.com

South East Asia

S-08-07 Persiaran Triangle
B Lepas, Penang 11900
Malaysia
Phone: +60 (12) 4302223
Email: info@caplinq.com