



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 12

LOCTITE ECCOBOND 3707 known as Hysol 3707 UV Edge bond
30ml

SDS No. : 362573
V002.0

Revision: 20.03.2017

printing date: 31.10.2019

Replaces version from: 29.10.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE ECCOBOND 3707 known as Hysol 3707 UV Edge bond 30ml

Contains:

3,4-Epoxy cyclohexyl methyl-3,4-epoxy cyclohexyl carboxylate
Aromatic sulfonium hexafluoro antimonate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Sample only.

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:	Warning
Hazard statement:	H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement:	P273 Avoid release to the environment.
Prevention	P280 Wear protective gloves.
Precautionary statement:	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
Response	P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
3,4-Epoxy cyclohexyl methyl-3,4-epoxy cyclohexyl carboxylate 2386-87-0	219-207-4 01-2119846133-44	$\geq 25 - < 50 \%$	Skin Sens. 1; Dermal H317 Aquatic Chronic 3 H412
Butane-1,4-diol 110-63-4	203-786-5 01-2119471849-20	$\geq 1 - < 10 \%$	Acute Tox. 4; Oral H302 STOT SE 3 H336
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	219-784-2 01-2119513212-58	$\geq 1 - < 2,5 \%$	Eye Dam. 1 H318
Aromatic sulfonium hexafluoro antimonate 159120-95-3	403-500-0	$\geq 0,25 - < 1 \%$	Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Skin Sens. 1 H317

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

In case of fire, keep containers cool with water spray.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.3. Specific end use(s)

Sample only.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silica, vitreous 60676-86-0 [SILICA, FUSED, RESPIRABLE DUST]		0,08	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure LimitsValid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silica, vitreous 60676-86-0 [SILICA, FUSED, RESPIRABLE DUST]		0,08	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Butane-1,4-diol 110-63-4	aqua (marine water)		0,0813 mg/l				
Butane-1,4-diol 110-63-4	aqua (intermittent releases)		8,13 mg/l				
Butane-1,4-diol 110-63-4	sediment (freshwater)				3,61 mg/kg		
Butane-1,4-diol 110-63-4	sediment (marine water)				0,361 mg/kg		
Butane-1,4-diol 110-63-4	soil				0,244 mg/kg		
Butane-1,4-diol 110-63-4	sewage treatment plant (STP)		1554 mg/l				
Butane-1,4-diol 110-63-4	aqua (freshwater)		0,813 mg/l				
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (freshwater)		1 mg/l				
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (marine water)		0,1 mg/l				
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (intermittent releases)		1 mg/l				
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	soil				0,13 mg/kg		
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	sewage treatment plant (STP)		10 mg/l				
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	sediment (freshwater)				3,6 mg/kg		
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	sediment (marine water)				0,36 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Butane-1,4-diol 110-63-4	Workers	dermal	Long term exposure - systemic effects		19 mg/kg	
Butane-1,4-diol 110-63-4	Workers	Inhalation	Long term exposure - systemic effects		136 mg/m3	
Butane-1,4-diol 110-63-4	Workers	inhalation	Acute/short term exposure - systemic effects		958 mg/m3	
Butane-1,4-diol 110-63-4	General population	Inhalation	Acute/short term exposure - systemic effects		340 mg/m3	
Butane-1,4-diol 110-63-4	General population	inhalation	Long term exposure - systemic effects		29 mg/m3	
Butane-1,4-diol 110-63-4	General population	dermal	Long term exposure - systemic effects		8 mg/kg	
Butane-1,4-diol 110-63-4	General population	oral	Long term exposure - systemic effects		8 mg/kg	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Workers	dermal	Acute/short term exposure - systemic effects		21 mg/kg	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Workers	Inhalation	Acute/short term exposure - systemic effects		147 mg/m3	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Workers	dermal	Long term exposure - systemic effects		21 mg/kg	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Workers	Inhalation	Long term exposure - systemic effects		147 mg/m3	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	inhalation	Long term exposure - systemic effects		43,5 mg/m3	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	inhalation	Acute/short term exposure - systemic effects		43,5 mg/m3	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	dermal	Long term exposure - systemic effects		12,5 mg/kg	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	dermal	Acute/short term exposure - systemic effects		12,5 mg/kg	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	paste liquid Clear
Odor	mild
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	> 93,33 °C (> 199,99 °F)Estimated
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density	No data available / Not applicable
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reacts with alcohols and amines.

Reacts with oxidants, acids and lyes

Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if stored and applied as directed.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

Hydrocarbons

carbon oxides.

nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****General toxicological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

May cause irritation to respiratory system.

Skin irritation:

Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Causes serious eye irritation.

Sensitizing:

May cause an allergic skin reaction.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
3,4-Epoxy cyclohexyl methyl-3,4-epoxy cyclohexyl carboxylate 2386-87-0	LD50	5.000 mg/kg	oral		rat	not specified
Butane-1,4-diol 110-63-4	LD50	1.500 mg/kg	oral		rat	BASF Test
[3-(2,3- Epoxypoxy)propyl]tri methoxysilane 2530-83-8	LD50	8.025 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Butane-1,4-diol 110-63-4	LC50	> 5,1 mg/l	aerosol	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LC50	> 5,3 mg/l	aerosol	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Butane-1,4-diol 110-63-4	LD50	> 2.000 mg/kg	dermal		rat	BASF Test
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LD50	4.250 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	highly irritating	20 s	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Butane-1,4-diol 110-63-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	A mutagenic potential can not be excluded.	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	A mutagenic potential can not be excluded.			mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL=500 mg/kg	oral: unspecified	28 d	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL=0,225 mg/kg	inhalation	14 d	rat	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Harmful to aquatic life with long lasting effects.

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
3,4-Epoxy cyclohexyl methyl- 3,4-epoxy cyclohexyl carboxylate 2386-87-0	LC50	24 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,4-Epoxy cyclohexyl methyl- 3,4-epoxy cyclohexyl carboxylate 2386-87-0	EC50	40 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,4-Epoxy cyclohexyl methyl- 3,4-epoxy cyclohexyl carboxylate 2386-87-0	EC50	90 mg/l	Algae		Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butane-1,4-diol 110-63-4	LC50	> 10.000 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butane-1,4-diol 110-63-4	EC50	> 500 mg/l	Daphnia	24 h	other aquatic arthropod:	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butane-1,4-diol 110-63-4	EC50	> 500 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC10	83 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butane-1,4-diol 110-63-4	EC10	10.000 mg/l	Bacteria	16 h		not specified
Butane-1,4-diol 110-63-4	NOEC	> 85 mg/l	chronic Daphnia	21 d	Daphnia magna	not specified
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	LC50	55 mg/l	Fish	96 h	Cyprinus carpio	EU Method C.1 (Acute Toxicity for Fish)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	EC50	324 mg/l	Daphnia	48 h	Simocephalus vetulus	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	EC50	119 mg/l	Algae	7 d	Anabaena flos-aquae	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC10	40 mg/l	Algae	7 d	Anabaena flos-aquae	OECD Guideline 201 (Alga, Growth Inhibition Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	NOEC	> 100 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	NOEC	100 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

12.2. Persistence and degradability

Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
---------------------------------	--------	-------------------------	---------------	--------

3,4-Epoxy cyclohexyl methyl- 3,4-epoxy cyclohexyl carboxylate 2386-87-0		aerobic	71 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Butane-1,4-diol 110-63-4	readily biodegradable	aerobic	74 - 96 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
	inherently biodegradable	aerobic	90 - 100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	Not readily biodegradable.	aerobic	37 %	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
3,4-Epoxy cyclohexyl methyl- 3,4-epoxy cyclohexyl carboxylate 2386-87-0	1,34				20 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)
Butane-1,4-diol 110-63-4	-0,88				25 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	0,5				20 °C	QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Butane-1,4-diol 110-63-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.