LINQTAPE PIT1SD-2RL



1 mil polyimide film with double sided silicone adhesive and a double release liner

- 1 mil polyimide film
- Silicone adhesive
- >6500V breakdown voltage

LINQTAPE[™] PIT1SD-2RL is a 1-mil, double-sided, double release-liner, high performance, high-temperature resistant, pressure sensitive polyimide tape designed for both permanent and temporary bonding in many high temperature applications. Polyimide tape is widely used in applications requiring high electrical insulation and an excellent balance of thermal, mechanical, chemical and electrical properties.

LINQTAPE[™] PIT1SD-2RL Tape comes in 33 meter (36 yard) rolls of varying widths. LINQTAPE PIT-S polyimide tapes are available in a range of thicknesses, starting from 0.5 mil (12.7µm) thickness and up. Custom thicknesses are available upon request.

Specifications

Property	Value	Unit
Color	Amber	-
Adhesive Type	Silicone	-
Film Thickness	25.4 (1)	um (mil)
Adhesive Thickness	38.1 (1.5)	um (mil)
Release liner	Double	-
Total Thickness	101.6 (4)	um (mil)
Temperature Resistance	260	°C
Adhesion to Steel	25	oz/in
Breakdown Voltage	6500	Volts
Dielectric Constant (1 khz)	3-4	-
Dissipation Factor (1khz)	4.0 x 10 ⁻³	-

Storage and Handling

Shelf life is 1 year if stored in a dry and cool, well ventilated place at room temperature.

The product is supplied in rolls and should be kept in a cool $(10^{\circ}C - 25^{\circ}C)$ dry place (40% - 75% humidity) away from direct sunlight or temperature extremes. Once removed from packaging it should be protected against dust and other impurities.

Europe

Industrieweg 15E, 1566JN Assendelft The Netherlands Phone: +31 (20) 893 2224 Email: info@capling.com Canada 80 Sirocco Crescent Ottawa ON, K2S 2C9 Canada Phone: +1 (613) 482-2215 Email: info@caplinq.com



North America 36927 Schoolcraft Rd Livonia, MI 48150 United States Phone: +1 (313) 558-8243 Email: info@caplinq.com South East Asia

S-08-07 Persiaran Triangle B Lepas, Penang 11900 Malaysia Phone: +60 (12)4302223 Email: info@caplinq.com