

Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 25

SDS No.: 153624

V008.0

Revision: 04.01.2017

printing date: 18.12.2019

Replaces version from: 26.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE AA 3526 LC known as Loctite 3526 Heat/ UV

LOCTITE AA 3526 LC known as Loctite 3526 Heat/ UV

Contains:

2-Hydroxyethyl methacrylate

Isobornyl acrylate

(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

Hydroxypropyl methacrylate

Tert-butyl perbenzoate

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide

Acrylic acid

2-Hydroxyethyl acrylate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Ultraviolet adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Belgium N.V.

Esplanade 1

1020 Brussels

Belgium

Phone: +32 (2) 421 2711 Fax-no.: +32 (2) 420 7025

ua-products a fety. uk @uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

V008.0

MSDS-No.: 153624

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Toxic to reproduction Category 2

H361f Suspected of damaging fertility.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:	(!) ★	

Signal word: Warning

Hazard statement:	H315 Causes skin irritation.
Hazai u Statement.	
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H335 May cause respiratory irritation.
	H361f Suspected of damaging fertility.
	H411 Toxic to aquatic life with long lasting effects.

Precautionary statement:	P261 Avoid breathing vapours.
Prevention	P273 Avoid release to the environment.
	P280 Wear protective gloves/protective clothing.

Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
_	P337+P313 If eve irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

UV curing acrylic adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
2-Hydroxyethyl methacrylate 868-77-9	212-782-2 01-2119490169-29	10- 20 %	Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319
Isobornyl methacrylate 7534-94-3	231-403-1 01-2119886505-27	10- 20 %	Aquatic Chronic 3 H412
Isobornyl acrylate 5888-33-5	227-561-6 01-2119957862-25	5- < 10 %	Skin Irrit. 2 H315 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Sens. 1B H317 Aquatic Acute 1 H400 Aquatic Chronic 1 H410
Urethane acrylate		5- < 10 %	Eye Irrit. 2 H319
Hydroxypropyl methacrylate 27813-02-1	248-666-3 01-2119490226-37	1-< 5 %	Skin Sens. 1 H317 Eye Irrit. 2 H319
Tert-butyl perbenzoate 614-45-9	210-382-2 01-2119513317-46	1-< 5 %	Org. Perox. C H242 Skin Irrit. 2; Dermal H315 Acute Tox. 4; Inhalation H332 Skin Sens. 1 H317 Aquatic Acute 1 H400 Aquatic Chronic 3 H412
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	278-355-8 01-2119972295-29	1-< 5 %	Repr. 2 H361f Aquatic Chronic 2 H411 Skin Sens. 1B H317
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	256-032-2 01-2119484613-34	1-< 3 %	Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Skin Sens. 1 H317 Aquatic Chronic 2 H411
Acrylic acid 79-10-7	201-177-9 01-2119452449-31	1-< 3%	Flam. Liq. 3 H226 Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Corr. 1A H314 Acute Tox. 4; Inhalation H332 STOT SE 3

			H335 Aquatic Acute 1 H400 Aquatic Chronic 2 H411
Methacrylic acid 79-41-4	201-204-4 01-2119463884-26	0,1-< 1 %	Acute Tox. 4; Oral H302 Acute Tox. 3; Dermal H311 Acute Tox. 4; Inhalation H332 Skin Corr. 1A H314
2-Hydroxyethyl acrylate 818-61-1	212-454-9 01-2119459345-34	0,02-< 0,2 %	Acute Tox. 3; Dermal H311 Skin Corr. 1B H314 Skin Sens. 1 H317 Aquatic Acute 1 H400

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Consideration should be given to the possible effects of a faulty UV source (Stray radiation, ozone).

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Rash, Urticaria.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Ventilation will remove any ozone that may be produced by the ultra violet lamp

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

7.3. Specific end use(s)

Ultraviolet adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	143	Short Term Exposure Limit (STEL):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	72	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Acrylic acid 79-10-7 [ACRYLIC ACID]	2	6	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	70	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	140	Short Term Exposure Limit (STEL):		IR_OEL

$\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value			Remarks	
	- ompai tineit	F	mg/l	ppm	mg/kg	others	
2-Hydroxyethyl methacrylate 868-77-9	aqua (freshwater)					0,482 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	aqua (marine water)					0,482 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	sewage treatment plant (STP)					10 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	aqua (intermittent releases)					1 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	sediment (freshwater)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	sediment (marine water)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	soil				0,476 mg/kg		
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	aqua (freshwater)					4,66 μg/L	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	soil				0,118 mg/kg		
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	sewage treatment plant (STP)					2,45 mg/L	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	sediment (freshwater)				0,604 mg/kg		
Isobornyl acrylate 5888-33-5	aqua (freshwater)					0,00092 mg/L	
Isobornyl acrylate 5888-33-5	aqua (marine water)					0,000092 mg/L	
Isobornyl acrylate 5888-33-5	sewage treatment plant (STP)					2 mg/L	
Isobornyl acrylate 5888-33-5	aqua (intermittent releases)					0,00704 mg/L	
Isobornyl acrylate 5888-33-5	sediment (freshwater)				0,145 mg/kg		
Isobornyl acrylate 5888-33-5	sediment (marine water)				0,0145 mg/kg		
Isobornyl acrylate 5888-33-5	soil				0,0285 mg/kg		
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (freshwater)					0,904 mg/L	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (marine water)					0,904 mg/L	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sewage treatment plant (STP)					10 mg/L	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (intermittent releases)					0,972 mg/L	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sediment (freshwater)				6,28 mg/kg		
Methacrylic acid, monoester with propane- 1,2-diol	sediment (marine water)				6,28 mg/kg		
27813-02-1 Methacrylic acid, monoester with propane- 1,2-diol	soil				0,727 mg/kg		
27813-02-1 Tert-butyl perbenzoate	aqua					0,008 mg/L	
614-45-9 Tert-butyl perbenzoate	(freshwater) aqua (marine					0,0008 mg/L	
614-45-9	water)						

MSDS-No.: 153624 LOCTITE AA 3526 LC known as Loctite 3526 Heat/ UV Page 8 of 25 V008.0 0,008 mg/L Tert-butyl perbenzoate aqua 614-45-9 (intermittent releases) Tert-butyl perbenzoate 0,6 mg/L sewage treatment plant 614-45-9 (STP) Tert-butyl perbenzoate sediment 0,22 mg/kg 614-45-9 (freshwater) Tert-butyl perbenzoate 0.022 sediment (marine water) 614-45-9 mg/kg 0,0393 Tert-butyl perbenzoate soil 614-45-9 mg/kg Tert-butyl perbenzoate oral 6,67 mg/kg 614-45-9 Diphenyl(2,4,6-trimethylbenzoyl)phosphine aqua 0,00353 mg/L oxide (freshwater) 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine aqua (marine 0,000353 oxide water) mg/L 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine aqua 0,0353 mg/L (intermittent oxide 75980-60-8 releases) Diphenyl(2,4,6-trimethylbenzoyl)phosphine 0,29 mg/kg sediment oxide (freshwater) 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine sediment 0,029 oxide (marine water) mg/kg 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine soil 0,0557 oxide mg/kg 75980-60-8 (1-Methyl-1,2-ethanediyl)bis[oxy(methyl-0,0073 mg/L aqua 2,1-ethanediyl)] diacrylate (freshwater) 42978-66-5 (1-Methyl-1,2-ethanediyl)bis[oxy(methylaqua (marine 0,0007 mg/L 2,1-ethanediyl)] diacrylate water) 42978-66-5 (1-Methyl-1,2-ethanediyl)bis[oxy(methyl-100 mg/L sewage 2,1-ethanediyl)] diacrylate treatment plant 42978-66-5 (STP) 0,73 mg/L (1-Methyl-1,2-ethanediyl)bis[oxy(methylaqua 2,1-ethanediyl)] diacrylate (intermittent 42978-66-5 releases) (1-Methyl-1,2-ethanediyl)bis[oxy(methylsoil 0,00243 2,1-ethanediyl)] diacrylate mg/kg 42978-66-5 (1-Methyl-1,2-ethanediyl)bis[oxy(methyl-0,19 mg/kg sediment 2,1-ethanediyl)] diacrylate (marine water) 42978-66-5 Acrylic acid 0,003 mg/L aqua 79-10-7 (freshwater) Acrylic acid aqua (marine 0,0003 mg/L 79-10-7 water) Acrylic acid aqua 0,0013 mg/L 79-10-7 (intermittent releases) 0,9 mg/L Acrylic acid sewage 79-10-7 treatment plant (STP) Acrylic acid sediment 0,0236 79-10-7 (freshwater) mg/kg Acrylic acid sediment 0,00236 79-10-7 (marine water) mg/kg Acrylic acid soil 1 mg/kg 79-10-7 Acrylic acid 0,0023 oral 79-10-7 mg/kg 0,03 g/kg Acrylic acid Predator

0,82 mg/L

0,82 mg/L

10 mg/L

79-10-7 Methacrylic acid

79-41-4

79-41-4

79-41-4

Methacrylic acid

Methacrylic acid

aqua

water)

sewage

(freshwater)

aqua (marine

treatment plant

MSDS-No.: 153624

V008.0

	(STP)	
Methacrylic acid 79-41-4	aqua (intermittent releases)	0,82 mg/L
Methacrylic acid 79-41-4	soil	1,2 mg/kg
2-Hydroxyethyl acrylate 818-61-1	aqua (freshwater)	0,017 mg/L
2-Hydroxyethyl acrylate 818-61-1	aqua (marine water)	0,002 mg/L
2-Hydroxyethyl acrylate 818-61-1	aqua (intermittent releases)	0,036 mg/L
2-Hydroxyethyl acrylate 818-61-1	sediment (freshwater)	0,064 mg/kg
2-Hydroxyethyl acrylate 818-61-1	sediment (marine water)	0,006 mg/kg
2-Hydroxyethyl acrylate 818-61-1	soil	0,003 mg/kg
2-Hydroxyethyl acrylate 818-61-1	Sewage treatment plant	10 mg/L
2-Hydroxyethyl acrylate 818-61-1	Air	

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2-Hydroxyethyl methacrylate 868-77-9	Workers	dermal	Long term exposure - systemic effects		1,3 mg/kg bw/day	
2-Hydroxyethyl methacrylate 868-77-9	Workers	Inhalation	Long term exposure - systemic effects		4,9 mg/m3	
2-Hydroxyethyl methacrylate 868-77-9	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg bw/day	
2-Hydroxyethyl methacrylate 868-77-9	General population	Inhalation	Long term exposure - systemic effects		2,9 mg/m3	
2-Hydroxyethyl methacrylate 868-77-9	General population	oral	Long term exposure - systemic effects		0,83 mg/kg bw/day	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Workers	dermal	Long term exposure - systemic effects		1,04 mg/kg	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	General population	dermal	Long term exposure - systemic effects		0,625 mg/kg bw/day	
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - systemic effects		1,39 mg/kg bw/day	
Isobornyl acrylate 5888-33-5	General population	oral	Long term exposure - systemic effects		0,83 mg/kg bw/day	
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg bw/day	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg bw/day	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	Workers	Inhalation	Long term exposure - systemic effects		14,7 mg/m3	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg bw/day	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	Inhalation	Long term exposure - systemic effects		8,8 mg/m3	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	oral	Long term exposure - systemic effects		2,5 mg/kg bw/day	
Tert-butyl perbenzoate 614-45-9	Workers	Inhalation	Long term exposure - systemic effects		4 mg/m3	
Tert-butyl perbenzoate 614-45-9	Workers	dermal	Long term exposure - systemic effects		6,25 mg/kg bw/day	
Tert-butyl perbenzoate 614-45-9	General population	Inhalation	Acute/short term exposure - local effects		1 mg/m3	
Tert-butyl perbenzoate 614-45-9	General population	Inhalation	Acute/short term exposure - systemic effects		1 mg/m3	
Tert-butyl perbenzoate 614-45-9	General population	dermal	Long term exposure - systemic effects		3,125 mg/kg bw/day	
Tert-butyl perbenzoate 614-45-9	General population	oral	Long term exposure - systemic effects		0,625 mg/kg bw/day	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	Inhalation	Long term exposure - systemic effects		3,5 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	dermal	Long term exposure - systemic effects		1 mg/kg	
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	Workers	inhalation	Long term exposure -		24,48 mg/m3	

42978-66-5	1	į	systemic effects	1	ĺ
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Workers	dermal	Long term exposure - systemic effects	2,77 mg/kg	
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	General population	inhalation	Long term exposure - systemic effects	7,24 mg/m3	
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	General population	oral	Long term exposure - systemic effects	2,08 mg/kg	
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	General population	dermal	Long term exposure - systemic effects	1,66 mg/kg	
Acrylic acid 79-10-7	Workers	inhalation	Long term exposure - local effects	30 mg/m3	
Acrylic acid 79-10-7	Workers	inhalation	Acute/short term exposure - local effects	30 mg/m3	
Acrylic acid 79-10-7	Workers	dermal	Acute/short term exposure - local effects	1 mg/cm2	
Acrylic acid 79-10-7	General population	dermal	Acute/short term exposure - local effects	1 mg/cm2	
Acrylic acid 79-10-7	General population	inhalation	Acute/short term exposure - local effects	3,6 mg/m3	
Acrylic acid 79-10-7	General population	inhalation	Long term exposure - local effects	3,6 mg/m3	
Methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - local effects	88 mg/m3	
Methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - systemic effects	29,6 mg/m3	
Methacrylic acid 79-41-4	Workers	dermal	Long term exposure - systemic effects	4,25 mg/kg bw/day	
Methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - local effects	6,55 mg/m3	
Methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - systemic effects	6,3 mg/m3	
Methacrylic acid 79-41-4	General population	dermal	Long term exposure - systemic effects	2,55 mg/kg bw/day	
2-Hydroxyethyl acrylate 818-61-1	Workers	inhalation	Long term exposure - local effects	2,4 mg/m3	
2-Hydroxyethyl acrylate 818-61-1	General population	inhalation	Long term exposure - local effects	1,2 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

UV lamp should be designed, installed and operated in such a way as to eliminate exposure of the skin and eyes to stray radiation

Respiratory protection:

Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid light yellow Odor irritating, Sharp

Odour threshold No data available / Not applicable

pH No data available / Not applicable

Initial boiling point $> 149.0 \,^{\circ}\text{C} \, (> 300.2 \,^{\circ}\text{F})$

Flash point > 93,4 °C (> 200.12 °F); Tagliabue closed cup

Decomposition temperature No data available / Not applicable

Vapour pressure < 13,3322400 mbar

(24,0 °C (75.2 °F))

Density 1,0633 g/cm3

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable

Solubility (qualitative) Slight

(Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable Flammability No data available / Not applicable No data available / Not applicable Auto-ignition temperature Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate No data available / Not applicable No data available / Not applicable Vapor density No data available / Not applicable Oxidising properties

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use. Protect from direct sunlight.

Avoid contact with acids and oxidizing agents.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

STOT-single exposure:

May cause respiratory irritation.

Oral toxicity:

May cause irritation to the digestive tract.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye irritation.

Sensitizing:

May cause an allergic skin reaction.

Reproductive toxicity: Suspected of damaging fertility.

Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
2-Hydroxyethyl	LD50	> 5.000 mg/kg	oral		rat	not specified
methacrylate						
868-77-9						
Isobornyl methacrylate	LD50	3.160 mg/kg	oral		rat	not specified
7534-94-3						
Isobornyl acrylate	LD50	4.350 mg/kg	oral		rat	not specified
5888-33-5						
Hydroxypropyl	LD50	> 2.000 mg/kg	oral		rat	OECD Guideline 401 (Acute
methacrylate						Oral Toxicity)
27813-02-1						
Tert-butyl perbenzoate	LD50	4.838 mg/kg	oral		rat	not specified
614-45-9						
Diphenyl-2,4,6-	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute
trimethylbenzoyl						Oral Toxicity)
phosphine oxide						
75980-60-8						
(1-Methyl-1,2-	LD50	> 2.000 mg/kg	oral		rat	OECD Guideline 423 (Acute
ethanediyl)bis[oxy(methyl						Oral toxicity)
-2,1-ethanediyl)]						
diacrylate						
42978-66-5						
Acrylic acid	LD50	1.500 mg/kg	oral		rat	BASF Test
79-10-7						
Methacrylic acid	LD50	1.320 mg/kg	oral		rat	OECD Guideline 401 (Acute
79-41-4	I	ļ	ļ		Į	Oral Toxicity)

Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Tert-butyl perbenzoate	LC50	> 1,01 mg/l	aerosol		not specified	not specified
614-45-9						
Acrylic acid	LC50	> 5,1 mg/l	Vapor.	4 h	rat	OECD Guideline 403 (Acute
79-10-7						Inhalation Toxicity)
Acrylic acid	Acute	11 mg/l	vapour			Expert judgement
79-10-7	toxicity					
	estimate					
	(ATE)					
Methacrylic acid	LC50	> 3,6 mg/l	aerosol	4 h	rat	OECD Guideline 403 (Acute
79-41-4						Inhalation Toxicity)

Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
2-Hydroxyethyl methacrylate	LD50	> 3.000 mg/kg	dermal		rabbit	not specified
868-77-9 Isobornyl methacrylate 7534-94-3	LD50	> 3.000 mg/kg	dermal		rabbit	not specified
Isobornyl acrylate 5888-33-5	LD50	> 5.000 mg/kg	dermal		rabbit	not specified
Hydroxypropyl methacrylate 27813-02-1	LD50	> 5.000 mg/kg	dermal		rabbit	not specified
Tert-butyl perbenzoate 614-45-9	LD50	3.817 mg/kg	dermal		rat	not specified
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
(1-Methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate	LD50	> 2.000 mg/kg	dermal			OECD Guideline 402 (Acute Dermal Toxicity)
42978-66-5 Acrylic acid 79-10-7	Acute toxicity estimate	1.100 mg/kg	dermal			Expert judgement
Acrylic acid 79-10-7	(ATE) LD50	> 2.000 mg/kg			rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg	dermal			Expert judgement
Methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg			rabbit	Dermal Toxicity Screening

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	mildly irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Isobornyl acrylate 5888-33-5	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydroxypropyl methacrylate 27813-02-1	not irritating	24 h	rabbit	Draize Test
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not irritating	24 h	rabbit	not specified
(1-Methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Acrylic acid 79-10-7	highly corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Methacrylic acid 79-41-4	Category 1A (corrosive)	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
		ume		
Diphenyl-2,4,6-	not irritating		rabbit	not specified
trimethylbenzoyl				
phosphine oxide				
75980-60-8				
(1-Methyl-1,2-	moderately irritating		rabbit	OECD Guideline 405 (Acute
ethanediyl)bis[oxy(methyl				Eye Irritation / Corrosion)
-2,1-ethanediyl)]				
diacrylate				
42978-66-5				
Acrylic acid	corrosive	21 d	rabbit	BASF Test
79-10-7				
Methacrylic acid	Category I		rabbit	Draize Test
79-41-4				

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Isobornyl methacrylate 7534-94-3	not sensitising	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isobornyl acrylate 5888-33-5	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
(1-Methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	not specified
Acrylic acid 79-10-7	not sensitising	Skin painting test	guinea pig	not specified
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2-Hydroxyethyl acrylate 818-61-1	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	not specified

Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of administration	activation / Exposure time		
2-Hydroxyethyl	negative	bacterial reverse	with and without		OECD Guideline 471
methacrylate		mutation assay (e.g			(Bacterial Reverse Mutation
868-77-9		Ames test)			Assay)
	positive	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
		chromosome aberration test			Mammalian Chromosome Aberration Test)
Isobornyl methacrylate	negative	bacterial reverse	with and without		OECD Guideline 471
7534-94-3	negative	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
		Ames test)			Assay)
	negative	,	with and without		OECD Guideline 476 (In vitro
					Mammalian Cell Gene
					Mutation Test)
	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
77 1 1		aberration test	*4 1 *4 .		Aberration Test)
Hydroxypropyl methacrylate	negative	bacterial reverse	with and without		OECD Guideline 471 (Bacterial Reverse Mutation
27813-02-1		mutation assay (e.g Ames test)			Assay)
27013-02-1	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
	negative	gene mutation assay	with and without		Mammalian Cell Gene
		gene matation assay			Mutation Test)
Hydroxypropyl	negative	oral: gavage		rat	OECD Guideline 474
methacrylate					(Mammalian Erythrocyte
27813-02-1					Micronucleus Test)
Diphenyl-2,4,6-	negative	bacterial reverse	with and without		OECD Guideline 471
trimethylbenzoyl		mutation assay (e.g			(Bacterial Reverse Mutation
phosphine oxide		Ames test)			Assay)
75980-60-8		1 1 1	1.1 1 1.1		OF GD G '111' 472 G ''
	negative	in vitro mammalian chromosome	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome
		aberration test			Aberration Test)
	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
	negative	gene mutation assay	with and without		Mammalian Cell Gene
		<i>g.</i>			Mutation Test)
(1-Methyl-1,2-	negative	bacterial reverse	with and without		OECD Guideline 471
ethanediyl)bis[oxy(methyl		mutation assay (e.g			(Bacterial Reverse Mutation
-2,1-ethanediyl)]		Ames test)			Assay)
diacrylate					
42978-66-5	negative	bacterial reverse	with and without		OECD Guideline 476 (In vitro
	negative	mutation assay (e.g	with and without		Mammalian Cell Gene
		Ames test)			Mutation Test)
(1-Methyl-1,2-	negative	intraperitoneal		mouse	OECD Guideline 474
ethanediyl)bis[oxy(methyl		1			(Mammalian Erythrocyte
-2,1-ethanediyl)]					Micronucleus Test)
diacrylate					
42978-66-5		1 1	1.1 1 1.1		
Acrylic acid 79-10-7	negative	bacterial reverse mutation assay (e.g	with and without		not specified
/9-10-/		Ames test)			
Methacrylic acid	negative	bacterial reverse	with and without		OECD Guideline 471
79-41-4	guiive	mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)
Methacrylic acid	negative	inhalation		mouse	OECD Guideline 478 (Genetic
79-41-4	-				Toxicology: Rodent Dominant
					Lethal Test)
2-Hydroxyethyl acrylate	negative	bacterial reverse	with and without		not specified
818-61-1		mutation assay (e.g			
2-Hydroxyethyl acrylate	negative	Ames test) oral: gavage		mouse	OECD Guideline 474
818-61-1	negative	oran. gavage		mouse	(Mammalian Erythrocyte
818-01-1					

Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure timeFrequenc y of treatment	Route of application	Method
Hydroxypropyl methacrylate 27813-02-1		rat	male	2 years (102 weeks) 6 hours/day, 5 days/week	inhalation	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

Hazardous substances CAS-No.	Result / Classification	Species	Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	NOAEL P = 25 mg/kg NOAEL F1 = 500 mg/kg	oral: gavage		rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL P = 400 mg/kg	two- generation study oral: gavage	until one day before sacrifice	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
(1-Methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	NOAEL P = 250 mg/kg	screening oral: gavage	28 - 52 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Hydroxypropyl methacrylate 27813-02-1	NOAEL=300 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	NOAEL=100 mg/kg	oral: gavage	3 m5 d/w	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
(1-Methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	NOAEL=250 mg/kg	oral: gavage	28 - 52 ddaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Do not empty into drains / surface water / ground water.

Toxic to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
2-Hydroxyethyl methacrylate	LC50	227 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline
868-77-9						203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl methacrylate	EC50	380 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
868-77-9						202 (Daphnia sp. Acute
						Immobilisation
2-Hydroxyethyl methacrylate	EC50	345 mg/l	Algae	72 h	Selenastrum capricornutum	Test) OECD Guideline
868-77-9					(new name: Pseudokirchnerella subcapitata)	201 (Alga, Growth Inhibition Test)
	NOEC	160 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
					(new name: Pseudokirchnerella subcapitata)	201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate	EC0	> 3.000 mg/l	Bacteria	16 h	subcapitata)	not specified
868-77-9 2-Hydroxyethyl methacrylate	NOEC	24,1 mg/l	chronic	21 d	Daphnia magna	OECD 211
868-77-9		_ ,, g -	Daphnia			(Daphnia magna,
Isobornyl methacrylate	LC50	1,79 mg/l	Fish	96 h	Danio rerio	Reproduction Test) OECD Guideline
7534-94-3						203 (Fish, Acute
Isobornyl methacrylate	EC50	1,1 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline
7534-94-3						202 (Daphnia sp. Acute
						Immobilisation
Isobornyl methacrylate	EC50	2,66 mg/l	Algae	96 h	Pseudokirchnerella subcapitata	Test) OECD Guideline
7534-94-3	2000	2,00 mg/1	1 iigue	7011	1 seudomiemerem succuprum	201 (Alga, Growth
	NOEC	0,254 mg/l	Algae	96 h	Pseudokirchnerella subcapitata	Inhibition Test) OECD Guideline
		, ,			1	201 (Alga, Growth
Isobornyl methacrylate	NOEC	0,233 mg/l	chronic	21 d	Daphnia magna	Inhibition Test) OECD 211
7534-94-3			Daphnia			(Daphnia magna, Reproduction Test)
Isobornyl acrylate	LC50	0,704 mg/l	Fish	96 h	Danio rerio	OECD Guideline
5888-33-5						203 (Fish, Acute Toxicity Test)
Isobornyl acrylate	EC50	1 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
5888-33-5						202 (Daphnia sp. Acute
						Immobilisation Test)
Isobornyl acrylate	NOEC	0,405 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
5888-33-5						201 (Alga, Growth Inhibition Test)
	EC50	1,98 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
						201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	NOEC	0,092 mg/l	chronic	21 d	Daphnia magna	OECD 211
J			Daphnia			(Daphnia magna, Reproduction Test)
Hydroxypropyl methacrylate 27813-02-1	LC50	493 mg/l	Fish	48 h	Leuciscus idus melanotus	DIN 38412-15
Hydroxypropyl methacrylate	EC50	> 143 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
27813-02-1						202 (Daphnia sp. Acute
						Immobilisation Toot)
Hydroxypropyl methacrylate	EC50	> 97,2 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline
27813-02-1						201 (Alga, Growth Inhibition Test)
	NOEC	> 97,2 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
						201 (Alga, Growth Inhibition Test)
Hydroxypropyl methacrylate	EC10	1.140 mg/l	Bacteria	16 h		not specified
27813-02-1 Hydroxypropyl methacrylate	NOEC	45,2 mg/l	chronic	21 d	Daphnia magna	OECD 211
27813-02-1		_	Daphnia			(Daphnia magna, Reproduction Test)
Tert-butyl perbenzoate	LC50	1,6 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
614-45-9					Danio rerio)	203 (Fish, Acute Toxicity Test)
Tert-butyl perbenzoate	EC50	11 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline

614-45-9			ĺ	ĺ	ĺ	202 (Daphnia sp.
						Acute Immobilisation
Tert-butyl perbenzoate 614-45-9	NOEC	0,72 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth
	EC50	0,8 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Inhibition Test) OECD Guideline 201 (Alga, Growth
Tert-butyl perbenzoate 614-45-9	EC10	6 mg/l	Bacteria	30 min	activated sludge of a predominantly domestic sewage	Sludge, Respiration
Tert-butyl perbenzoate 614-45-9	NOEC	0,44 mg/l	chronic Daphnia	21 d	Daphnia magna	Inhibition Test) OECD 211 (Daphnia magna,
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide	LC50	> 1 - 10 mg/l	Fish	48 h	Oryzias latipes	Reproduction Test) OECD Guideline 203 (Fish, Acute Toxicity Test)
75980-60-8 Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	> 10 - 100 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide	EC50	> 10 - 100 mg/l	Algae	72 h		Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
75980-60-8 Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide	EC 50	> 1.000 mg/l	Bacteria	30 min		OECD Guideline 209 (Activated Sludge, Respiration
75980-60-8 (1-Methyl-1,2- ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate 42978-66-5	LC50	> 4,5 - 10 mg/l	Fish	96 h	Leuciscus idus	Inhibition Test) DIN 38412-15
(1-Methyl-1,2- ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate 42978-66-5	EC50	88,7 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
(1-Methyl-1,2- ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	EC50	28 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
42978-66-5 (1-Methyl-1,2- ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	EC 50	> 10.000 mg/l	Bacteria	30 min		not specified
42978-66-5 Acrylic acid 79-10-7	LC50	27 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity
Acrylic acid 79-10-7	EC10	0,03 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC50	0,13 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Acrylic acid 79-10-7	EC10	41 mg/l	Bacteria	16 h	subspicurus)	not specified
Acrylic acid 79-10-7	NOEC	19 mg/l	chronic Daphnia	21 d	Daphnia magna	EPA OTS 797.1330 (Daphnid Chronic Toxicity
Methacrylic acid 79-41-4	LC50	85 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	Test) EPA OTS 797.1400 (Fish Acute Toxicity
Methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	Test) EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater
Methacrylic acid	NOEC	8,2 mg/l	Algae	72 h	Selenastrum capricornutum	Daphnids) OECD Guideline

79-41-4					(new name: Pseudokirchnerella	
					subcapitata)	Inhibition Test)
	EC50	45 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
					(new name: Pseudokirchnerella	201 (Alga, Growth
					subcapitata)	Inhibition Test)
Methacrylic acid 79-41-4	EC10	100 mg/l	Bacteria	17 h		not specified
2-Hydroxyethyl acrylate	LC50	4,8 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline
818-61-1						203 (Fish, Acute
						Toxicity Test)
2-Hydroxyethyl acrylate	EC50	0,78 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
818-61-1						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
2-Hydroxyethyl acrylate	EC50	6 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
818-61-1						201 (Alga, Growth
						Inhibition Test)
	NOEC	1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
						201 (Alga, Growth
						Inhibition Test)
2-Hydroxyethyl acrylate	EC10	> 100 mg/l	Bacteria	72 h	activated sludge, domestic	other guideline:
818-61-1						
2-Hydroxyethyl acrylate	NOEC	0,86 mg/l	chronic	21 d	Daphnia magna	OECD 211
818-61-1			Daphnia			(Daphnia magna,
						Reproduction Test)

12.2. Persistence and degradability

Persistence and Biodegradability: The product is not biodegradable.

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

MSDS-No.: 153624

V008.0

2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Isobornyl methacrylate 7534-94-3	readily biodegradable	aerobic	70 %	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Isobornyl acrylate 5888-33-5		no data	72,9 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydroxypropyl methacrylate 27813-02-1	readily biodegradable	aerobic	94,2 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Tert-butyl perbenzoate 614-45-9	readily biodegradable	aerobic	70 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8			< 20 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
(1-Methyl-1,2- ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate 42978-66-5	inherently biodegradable	aerobic	> 90 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
		aerobic	48 %	EU Method C.4-C (Determination of the "Ready" BiodegradabilityCarbon Dioxide Evolution Test)
Acrylic acid 79-10-7	readily biodegradable	aerobic	81 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-Hydroxyethyl acrylate 818-61-1	readily biodegradable	aerobic	79 - 80 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Mobility: Cured adhesives are immobile.

Bioaccumulative potential: No data available for the product.

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

Isobornyl methacrylate 7534-94-3	5,09				OECD Guideline 117 (Partition Coefficient (n- octanol / water), HPLC Method)
Isobornyl acrylate 5888-33-5	4,52				OECD Guideline 117 (Partition Coefficient (noctanol / water), HPLC Method)
Hydroxypropyl methacrylate 27813-02-1	0,97			20 °C	not specified
Tert-butyl perbenzoate 614-45-9	3,00			25 °C	OECD Guideline 117 (Partition Coefficient (noctanol / water), HPLC Method)
Acrylic acid 79-10-7		3,16			not specified
Acrylic acid 79-10-7	0,46			25 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
Methacrylic acid 79-41-4	0,93			22 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
2-Hydroxyethyl acrylate 818-61-1	-0,17			25 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
2-Hydroxyethyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
868-77-9	Bioaccumulative (vPvB) criteria.
Isobornyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
7534-94-3	Bioaccumulative (vPvB) criteria.
Isobornyl acrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
5888-33-5	Bioaccumulative (vPvB) criteria.
Urethane acrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
	Bioaccumulative (vPvB) criteria.
Hydroxypropyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
27813-02-1	Bioaccumulative (vPvB) criteria.
Tert-butyl perbenzoate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
614-45-9	Bioaccumulative (vPvB) criteria.
Diphenyl-2,4,6-trimethylbenzoyl phosphine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
oxide	Bioaccumulative (vPvB) criteria.
75980-60-8	
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
ethanediyl)] diacrylate	Bioaccumulative (vPvB) criteria.
42978-66-5	
Acrylic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
79-10-7	Bioaccumulative (vPvB) criteria.
Methacrylic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
79-41-4	Bioaccumulative (vPvB) criteria.
2-Hydroxyethyl acrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
818-61-1	Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Collection and delivery to recycling enterprise or other registered elimination institution.

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBS	TANCE, LIQUID), N.O.S. (Isobornyl
-----	--------------------------------	---------------	-------------	-----------

methacrylate, Isobornyl acrylate)

RID ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl

 $methacrylate, Isobornyl\ acrylate)$

ADN ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl

methacrylate, Isobornyl acrylate)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl

methacrylate, Isobornyl acrylate)

IATA Environmentally hazardous substance, liquid, n.o.s. (Isobornyl methacrylate, Isobornyl

acrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	ç

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR not applicable

MSDS-No.: 153624

V008.0

Tunnelcode: (E) RID not applicable ADN not applicable **IMDG** not applicable not applicable **IATA**

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3.00 % (2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.