

ABP 8035(10.7g

Safety Data Sheet according to Regulation (EC) No 1907/2006

LOCTITE ABLESTIK ABP 8035 known as LOCTITE ABLESTIK

Page 1 of 12

SDS No.: 488052

V002.0

Revision: 17.07.2018

printing date: 22.07.2020

Replaces version from: 12.05.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE ABLESTIK ABP 8035 known as LOCTITE ABLESTIK ABP 8035(10.7g $\,$

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Silicone adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Contains

Supplemental information EUH210 Safety data sheet available on request.

Contains Epoxycyclohexylethyltrimethoxysilane. May produce an allergic reaction.

2.3. Other hazards

None if used properly.

This mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Octamethylcyclotetrasiloxane	209-136-7	0,1-< 1 %	Flam. Liq. 3
556-67-2	01-2119529238-36		H226
			Repr. 2
			H361f
			Aquatic Chronic 4
			H413
			====
			EU. REACH Candidate List of Substances of
			Very High Concern for Authorization
			(SVHC)
Epoxycyclohexylethyltrimethoxysilane	222-217-1	0,1-< 1 %	Skin Sens. 1B
3388-04-3			H317
			Muta. 2
			H341
			Carc. 2
			H351
			Aquatic Chronic 3
			H412

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

Silicon dioxide

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Remove sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Silicone adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

None

Occupational Exposure Limits

Valid for

Ireland

None

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental	Exposure	Value				Remarks
	Compartment	period					
			mg/l	ppm	mg/kg	others	
Octamethylcyclotetrasiloxane	aqua		0,0015				
556-67-2	(freshwater)		mg/l				
Octamethylcyclotetrasiloxane	aqua (marine		0,00015				
556-67-2	water)		mg/l				
Octamethylcyclotetrasiloxane 556-67-2	sewage treatment plant (STP)		10 mg/l				
Octamethylcyclotetrasiloxane 556-67-2	sediment (freshwater)				3 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	sediment (marine water)				0,3 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	oral				41 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	soil				0,54 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application	Route of	Health Effect	Exposure	Value	Remarks
	Area	Exposure		Time		
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - systemic effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - local effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Acute/short term exposure - systemic effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Acute/short term exposure - local effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - systemic effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - local effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Acute/short term exposure - systemic effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Acute/short term exposure - local effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Long term exposure - systemic effects		3,7 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Acute/short term exposure - systemic effects		3,7 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

8033(10.7

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid colourless
Odor mild

Odour threshold No data available / Not applicable

pН No data available / Not applicable Melting point No data available / Not applicable Solidification temperature No data available / Not applicable Initial boiling point No data available / Not applicable > 93 °C (> 199.4 °F); Estimated Flash point No data available / Not applicable Evaporation rate Flammability No data available / Not applicable Explosive limits No data available / Not applicable No data available / Not applicable Vapour pressure Relative vapour density: No data available / Not applicable

Density 1,07 g/cm3

()

Bulk density

No data available / Not applicable
Solubility

No data available / Not applicable

Solubility (qualitative)

(Solvent: Water)

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable
Oxidising properties

No data available / Not applicable
No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

Insoluble

10.1. Reactivity

Reacts with oxidants, acids and lyes

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Excessive heat.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Octamethylcyclotetrasilox	LD50	> 4.800 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
ane				
556-67-2				
Epoxycyclohexylethyltri	LD50	13.000 mg/kg	rat	
methoxysilane				
3388-04-3				

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Octamethylcyclotetrasilox ane 556-67-2	LD50	> 2.400 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Epoxycyclohexylethyltri methoxysilane 3388-04-3	LD50	6.700 mg/kg	rabbit	

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Octamethylcyclotetrasilox	LC50	36 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
ane						Inhalation Toxicity)
556-67-2						

Skin corrosion/irritation:

No data available.

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Octamethylcyclotetrasilox	not irritating		rabbit	Draize Test
ane				
556-67-2				

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
Octamethylcyclotetrasilox	not sensitising	not specified		Magnusson and Kligman Method
ane				
556-67-2				
Epoxycyclohexylethyltri methoxysilane	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
3388-04-3				

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of	Metabolic activation /	Species	Method
		administration	Exposure time		
Octamethylcyclotetrasilox	positive	bacterial gene	with and without		not specified
ane		mutation assay			
556-67-2					
Octamethylcyclotetrasilox	positive	sister chromatid	with and without		not specified
ane		exchange assay in			
556-67-2		mammalian cells			
Octamethylcyclotetrasilox	negative	in vitro mammalian	with and without		not specified
ane		chromosome			
556-67-2		aberration test			

ane	positive	mutation assay	with and without	not specified
556-67-2		mutation assay		
Octamethylcyclotetrasilox	positive	sister chromatid	with and without	not specified
ane		exchange assay in		
556-67-2		mammalian cells		
Octamethylcyclotetrasilox	negative	in vitro mammalian	with and without	not specified
ane		chromosome		
556-67-2		aberration test		

	rcin	$\alpha \alpha c$	mı	•1 1 T T 7
$\sim a$	11 (111	UZU	ш	JIL 9

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Octamethylcyclotetrasilox	LOAEL 35 ppm	inhalation	6 h nose only	rat	OECD Guideline 412
ane			inhalation		(Repeated Dose
556-67-2			5 days/week for 13		Inhalation Toxicity:
			weeks		28/14-Day)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Octamethylcyclotetrasiloxane 556-67-2	NOEC	0,0044 mg/l	93 d	Salmo gairdneri (new name: Oncorhynchus mykiss)	other guideline:
Octamethylcyclotetrasiloxane 556-67-2	LC50		96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish Acute Toxicity Test)
Epoxycyclohexylethyltrimetho xysilane 3388-04-3	LC50	42,3 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Octamethylcyclotetrasiloxane	EC50		48 h	Daphnia magna	EPA OTS 797.1300
556-67-2					(Aquatic Invertebrate Acute
					Toxicity Test, Freshwater
					Daphnids)
Epoxycyclohexylethyltrimetho	EC50	58 mg/l	48 h	Daphnia magna	OECD Guideline 202
xysilane					(Daphnia sp. Acute
3388-04-3					Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

~.~	Value type	Value	Exposure time	Species	Method
Octamethylcyclotetrasiloxane 556-67-2	NOEC	7.9 μg/l	21 d	1	EPA OTS 797.1330 (Daphnid Chronic Toxicity Test)
Epoxycyclohexylethyltrimetho xysilane 3388-04-3	NOEC	16 mg/l	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Octamethylcyclotetrasiloxane 556-67-2	EC50		96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Octamethylcyclotetrasiloxane 556-67-2	NOEC	< 0,022 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Epoxycyclohexylethyltrimetho xysilane 3388-04-3	NOEC	6 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Epoxycyclohexylethyltrimetho xysilane 3388-04-3	EC50	90 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Octamethylcyclotetrasiloxane 556-67-2	EC50		3 h	activated sludge	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
Epoxycyclohexylethyltrimetho xysilane 3388-04-3	EC 50	> 100 mg/l	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
Octamethylcyclotetrasiloxane	not readily biodegradable.	aerobic	3,7 %	29 d	OECD Guideline 310 (Ready
556-67-2					BiodegradabilityCO2 in Sealed
					Vessels (Headspace Test)
Epoxycyclohexylethyltrimetho		aerobic	28 %	28 d	OECD Guideline 301 D (Ready
xysilane					Biodegradability: Closed Bottle
3388-04-3					Test)

12.3. Bioaccumulative potential

No data available.

Hazardous substances	Bioconcentratio	Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)				
Octamethylcyclotetrasiloxane	12.400	28 d		Pimephales	EPA OTS 797.1520 (Fish
556-67-2				promelas	Bioconcentration Test-Rainbow
				_	Trout)

12.4. Mobility in soil

Cured adhesives are immobile.

8035(10.79
-------	-------

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Octamethylcyclotetrasiloxane	6,488	25,1 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-
556-67-2			Stirring Method)
Epoxycyclohexylethyltrimetho	4,1	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
xysilane			Method)
3388-04-3			

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Octamethylcyclotetrasiloxane 556-67-2	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. **UN** number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. **Environmental hazards**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC) < 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H361f Suspected of damaging fertility.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.