

E/C/J

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 21

SDS No.: 454053

V007.0

Revision: 03.04.2019

printing date: 20.08.2020

Replaces version from: 02.04.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE ECCOBOND UV 9060F known as UV9060F 55CC EFD E/C/J

LOCTITE ECCOBOND UV 9060F known as UV9060F 55CC EFD

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Sample only.

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

# 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (CLP):

Acute toxicity Category 4

H302 Harmful if swallowed. Route of Exposure: Oral

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye damage Category 1

H318 Causes serious eye damage.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

#### Label elements (CLP):

Hazard pictogram:



**Contains** Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23

Mix of 2-hydroxyethyl acrylate and aliphatic isocyanate

Isobornyl acrylate

2-Propenamide, N,N-dimethyl-2-Hydroxy-2-methylpropiophenone

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide

Triphenyl phosphite

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Signal word: Danger

**Hazard statement:** H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction. Supplemental information

**Precautionary statement:** P261 Avoid breathing vapors.

P273 Avoid release to the environment. Prevention

P280 Wear protective gloves/eye protection.

**Precautionary statement:** 

P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove Response

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

## 2.3. Other hazards

Care should be taken during the cure of these products by UV radiation to avoid exposure of the skin and especially of the eyes to direct or reflected UV radiation as long term effects could be harmful.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	500-060-2 01-2119485796-17	10- 20 %	Acute Tox. 4 H332 STOT SE 3 H335
			Skin Sens. 1 H317
Mix of 2-hydroxyethyl acrylate and aliphatic isocyanate 264888-31-5		25- 50 %	Aquatic Chronic 3 H412 Skin Sens. 1 H317
Isobornyl acrylate 5888-33-5	227-561-6 01-2119957862-25	10- 20 %	Skin Irrit. 2 H315 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Sens. 1B H317 Aquatic Acute 1 H400 Aquatic Chronic 1 H410
2-Propenamide, N,N-dimethyl- 2680-03-7	220-237-5 01-2119971262-39	10- 20 %	Acute Tox. 3; Oral H301 Acute Tox. 3; Dermal H311 Eye Dam. 1 H318
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	246-386-6 01-2120000336-73	1-< 5 %	Aquatic Chronic 1 H410 Aquatic Acute 1 H400
2-Hydroxy-2-methylpropiophenone 7473-98-5	231-272-0 01-2119472306-39	0,25-< 2,5 %	Aquatic Chronic 3 H412 Acute Tox. 4; Oral H302
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	278-355-8 01-2119972295-29	0,25-< 2,5 %	Repr. 2 H361f Aquatic Chronic 2 H411 Skin Sens. 1B H317
p-Toluenesulphonyl isocyanate 4083-64-1	223-810-8 01-2119980050-47	0,1-< 1 %	Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334
Triphenyl phosphite 101-02-0	202-908-4 01-2119511213-58	0,1-< 1 %	Acute Tox. 4 H302 Eye Irrit. 2 H319 Skin Irrit. 2 H315 STOT RE 2 H373 Skin Sens. 1A H317 Aquatic Acute 1 H400 Aquatic Chronic 1 H410
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	423-340-5 01-2119489401-38 01-2119936813-33	0,25-< 2,5 %	Skin Sens. 1 H317 Aquatic Chronic 4 H413

Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

## Suitable extinguishing media:

water, carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

In case of fire, keep containers cool with water spray.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

## 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

#### Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Refer to Technical Data Sheet

# 7.3. Specific end use(s)

Sample only.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL

## **Occupational Exposure Limits**

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide		6	Time Weighted Average		IR_OEL
7631-86-9			(TWA):		
[SILICA, AMORPHOUS, TOTAL INHALABLE DUST]					
Silicon dioxide		2,4	Time Weighted Average		IR_OEL
7631-86-9			(TWA):		
[SILICA, AMORPHOUS, RESPIRABLE DUST]					

# **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	aqua (freshwater)		0,127 mg/l				
Hexane, 1,6-diisocyanato-, homopolymer	aqua (marine		0,0127				
28182-81-2	water)		mg/l				
Hexane, 1,6-diisocyanato-, homopolymer	aqua		1,27 mg/l				
28182-81-2	(intermittent releases)						
Hexane, 1,6-diisocyanato-, homopolymer	sediment				266700		
28182-81-2	(freshwater)				mg/kg		
Hexane, 1,6-diisocyanato-, homopolymer	sediment				26670		
28182-81-2	(marine water)				mg/kg		
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	Soil				53182 mg/kg		
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	sewage treatment plant (STP)		38,28 mg/l				
Isobornyl acrylate 5888-33-5	aqua (freshwater)		0,00092 mg/l				
Isobornyl acrylate	aqua (marine		0,000092	1			
5888-33-5	water)	<u>L</u>	mg/l			<u>L</u>	
Isobornyl acrylate	sewage		2 mg/l				
5888-33-5	treatment plant (STP)						
Isobornyl acrylate	aqua		0,00704	1			
5888-33-5	(intermittent releases)		mg/l				
Isobornyl acrylate	sediment				0,145		
5888-33-5	(freshwater)				mg/kg		
Isobornyl acrylate	sediment				0,0145		
5888-33-5	(marine water)				mg/kg		
Isobornyl acrylate	Soil				0,0285		
5888-33-5	A ·				mg/kg		
Isobornyl acrylate 5888-33-5	Air						
Isobornyl acrylate 5888-33-5	Predator						
N,N-Dimethylacrylamide	aqua		0,12 mg/l				
2680-03-7 N,N-Dimethylacrylamide	(freshwater) aqua (marine		0,012 mg/l				
2680-03-7	water)		0,012 mg/1				
N,N-Dimethylacrylamide	aqua		1,2 mg/l				
2680-03-7	(intermittent releases)						
N,N-Dimethylacrylamide	sediment				0,509		
2680-03-7	(freshwater)				mg/kg		
N,N-Dimethylacrylamide	sediment				0,0509		
2680-03-7	(marine water)				mg/kg		
N,N-Dimethylacrylamide 2680-03-7	Soil				0,0313 mg/kg		
N,N-Dimethylacrylamide	sewage		18 mg/l		IIIg/Kg		+
2680-03-7	treatment plant (STP)		To mg/1				
N,N-Dimethylacrylamide 2680-03-7	Predator						
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	aqua (freshwater)		0,229 mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one	aqua		0,184 mg/l	+		<u> </u>	
24650-42-8	(intermittent releases)		0,101 mg1				
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	aqua (marine water)		0,0229 mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one	sewage		19,4 mg/l	+			
24650-42-8	treatment plant (STP)		19,4 mg/1				
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	sediment (freshwater)				8,87 mg/kg		
2,2-Dimethoxy-1,2-diphenylethan-1-one	sediment			1	0,887		
24650-42-8	(marine water)				mg/kg		
2,2-Dimethoxy-1,2-diphenylethan-1-one	Soil				1,64 mg/kg		

24650-42-8 2-Hydroxy-2-methylpropiophenone aqua 0,00195 7473-98-5 (freshwater) mg/l 2-Hydroxy-2-methylpropiophenone 0,000195 aqua (marine 7473-98-5 water) mg/l 2-Hydroxy-2-methylpropiophenone 0,0195 aqua 7473-98-5 (intermittent mg/l releases) 2-Hydroxy-2-methylpropiophenone 7473-98-5 0,00514 sediment (freshwater) mg/kg 2-Hydroxy-2-methylpropiophenone 7473-98-5 0,000514 sediment (marine water) mg/kg 2-Hydroxy-2-methylpropiophenone 0,000674 Soil 7473-98-5 mg/kg 2-Hydroxy-2-methylpropiophenone sewage 45 mg/l treatment plant 7473-98-5 (STP) Diphenyl(2,4,6-trimethylbenzoyl)phosphine 0,00353 aqua (freshwater) mg/l oxide 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine aqua (marine 0.000353 oxide mg/l water) 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine 0,0353 aqua (intermittent mg/l oxide 75980-60-8 releases) Diphenyl(2,4,6-trimethylbenzoyl)phosphine 0,29 mg/kg sediment oxide (freshwater) 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine sediment 0,029 (marine water) mg/kg 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine 0,0557 Soil oxide mg/kg 75980-60-8

# **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	Workers	Inhalation	Acute/short term exposure - local effects		1 mg/m3	
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	Workers	Inhalation	Long term exposure - local effects		0,5 mg/m3	
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - systemic effects		1,39 mg/kg	
Isobornyl acrylate 5888-33-5	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	
N,N-Dimethylacrylamide 2680-03-7	Workers	dermal	Long term exposure - systemic effects		0,357 mg/kg 357 µg/kg bw/day	
N,N-Dimethylacrylamide 2680-03-7	Workers	inhalation	Long term exposure - systemic effects		0,207 mg/m3	
N,N-Dimethylacrylamide 2680-03-7	General population	oral	Long term exposure - systemic effects		0,0147 mg/kg 14,7 µg/kg bw/day	
N,N-Dimethylacrylamide 2680-03-7	General population	dermal	Long term exposure - systemic effects		0,179 mg/kg 179 µg/kg bw/day	
N,N-Dimethylacrylamide 2680-03-7	General population	inhalation	Long term exposure - systemic effects		0,051 mg/m3	
2-Hydroxy-2-methylpropiophenone 7473-98-5	Workers	Inhalation	Acute/short term exposure - systemic effects		3,5 mg/m3	
2-Hydroxy-2-methylpropiophenone 7473-98-5	Workers	Inhalation	Long term exposure - systemic effects		3,5 mg/m3	
2-Hydroxy-2-methylpropiophenone 7473-98-5	Workers	dermal	Long term exposure - systemic effects		1,25 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	dermal	Long term exposure - systemic effects		1 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Workers	Inhalation	Long term exposure - systemic effects		21 mg/m3	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Workers	Inhalation	Acute/short term exposure - systemic effects		21 mg/m3	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Workers	dermal	Long term exposure - systemic effects		3,3 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Workers	dermal	Acute/short term exposure - systemic effects		3,3 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	inhalation	Long term exposure - systemic effects		5,2 mg/m3	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	dermal	Long term exposure - systemic effects		1,5 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	oral	Long term exposure - systemic effects		1,5 mg/kg	

#### **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

UV lamp should be designed, installed and operated in such a way as to eliminate exposure of the skin and eyes to stray radiation

#### Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

#### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

## Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance liquid blue Odor mild

Odour threshold No data available / Not applicable

pH Not available.
Melting point Not available.

Solidification temperature No data available / Not applicable

Initial boiling point Not available. Flash point 97 °C (206.6 °F)

Evaporation rate No data available / Not applicable Flammability No data available / Not applicable Explosive limits No data available / Not applicable

Vapour pressure Not available.

Relative vapour density: No data available / Not applicable

Density 1,12 g/cm3

()

Bulk density

No data available / Not applicable

Solubility

No data available / Not applicable

Solubility (qualitative) Not available.

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable

## 9.2. Other information

Ignition temperature Not available.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Reducing agents.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

## 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

Protect from direct sunlight.

## 10.5. Incompatible materials

See section reactivity.

## 10.6. Hazardous decomposition products

Hydrocarbons carbon oxides. nitrogen oxides

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

# Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	LD50	> 2.500 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Isobornyl acrylate 5888-33-5	LD50	4.350 mg/kg	rat	not specified
2-Propenamide, N,N-dimethyl- 2680-03-7	LD50	> 215 - 464 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	LD50	> 5.000 mg/kg	rat	not specified
2-Hydroxy-2- methylpropiophenone 7473-98-5	LD50	1.694 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
p-Toluenesulphonyl isocyanate 4083-64-1	LD50	2.600 mg/kg	rat	not specified
Triphenyl phosphite 101-02-0	LD50	1.590 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Phenyl bis(2,4,6- trimethylbenzoyl)- phosphine oxide 162881-26-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

# Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Isobornyl acrylate 5888-33-5	LD50	> 3.000 mg/kg	rabbit	other guideline:
2-Propenamide, N,N-dimethyl- 2680-03-7	LD50	500 mg/kg	rat	not specified
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	LD50	> 5.000 mg/kg	rat	not specified
2-Hydroxy-2- methylpropiophenone 7473-98-5	LD50	6.929 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Triphenyl phosphite 101-02-0	LD50	> 2.000 - < 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Phenyl bis(2,4,6- trimethylbenzoyl)- phosphine oxide 162881-26-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

# Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Hexane, 1,6-diisocyanato-	Acute	1,5 mg/l	dust/mist			Expert judgement
, homopolymer, V=2750-	toxicity					
4250 mPas/23	estimate					
28182-81-2	(ATE)					
Triphenyl phosphite	LC50	> 6,7 mg/l	dust/mist	1 h	rat	equivalent or similar to OECD
101-02-0						Guideline 403 (Acute
						Inhalation Toxicity)

## Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Propenamide, N,N-dimethyl- 2680-03-7	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Hydroxy-2- methylpropiophenone 7473-98-5	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not irritating	24 h	rabbit	not specified

# Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2-Propenamide, N,N-dimethyl- 2680-03-7	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-Hydroxy-2- methylpropiophenone 7473-98-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not irritating		rabbit	not specified

# Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
Isobornyl acrylate	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
5888-33-5		assay (LLNA)		Local Lymph Node Assay)
2-Propenamide, N,N-	not sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
dimethyl-		test		
2680-03-7				
2-Hydroxy-2-	not sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
methylpropiophenone		test		
7473-98-5				
Diphenyl-2,4,6-	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
trimethylbenzoyl		assay (LLNA)		Local Lymph Node Assay)
phosphine oxide				
75980-60-8				
Triphenyl phosphite	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
101-02-0		assay (LLNA)		Local Lymph Node Assay)
Triphenyl phosphite	sensitising	Guinea pig maximisation	guinea pig	EPA OPPTS 870.2600 (Skin
101-02-0		test		Sensitisation)

# Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobornyl acrylate 5888-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl acrylate 5888-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Propenamide, N,N-dimethyl-2680-03-7	negative		with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-Propenamide, N,N-dimethyl- 2680-03-7	negative		with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxy-2- methylpropiophenone 7473-98-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxy-2- methylpropiophenone 7473-98-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Hydroxy-2- methylpropiophenone 7473-98-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
p-Toluenesulphonyl isocyanate 4083-64-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
p-Toluenesulphonyl isocyanate 4083-64-1	negative	in vitro mammalian chromosome aberration test	with and without		not specified

# Carcinogenicity

No data available.

# Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Isobornyl acrylate	NOAEL P 100 mg/kg		oral: gavage	rat	OECD Guideline 422
5888-33-5					(Combined Repeated Dose
	NOAEL F1 100 mg/kg				Toxicity Study with the
					Reproduction /
					Developmental Toxicity
					Screening Test)
2-Propenamide, N,N-	NOAEL P 5 mg/kg		oral: gavage	rat	OECD Guideline 421
dimethyl-					(Reproduction /
2680-03-7	NOAEL F1 30 mg/kg				Developmental Toxicity
					Screening Test)
p-Toluenesulphonyl	NOAEL F1 300 mg/kg	one-	oral: gavage	rat	OECD Guideline 422
isocyanate		generation			(Combined Repeated Dose
4083-64-1		study			Toxicity Study with the
					Reproduction /
					Developmental Toxicity
					Screening Test)

# STOT-single exposure:

No data available.

# STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Isobornyl acrylate 5888-33-5	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Propenamide, N,N-dimethyl- 2680-03-7	NOAEL 10 mg/kg	dermal	13 weeks 6 hours/day, 7 days/week	rat	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
2-Hydroxy-2- methylpropiophenone 7473-98-5	NOAEL 50 mg/kg	oral: gavage	92-93 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	NOAEL 100 mg/kg	oral: gavage	3 m 5 d/w	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Triphenyl phosphite 101-02-0	NOAEL 15 mg/kg	oral: gavage	16 weeks daily	rat	equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reprod./Develop. Tox. Screening Test)

# **Aspiration hazard:**

No data available.

# **SECTION 12: Ecological information**

# General ecological information:

Do not empty into drains / surface water / ground water.

# 12.1. Toxicity

# **Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	LC50	> 100 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Mix of 2-hydroxyethyl acrylate and aliphatic isocyanate 264888-31-5	LC50	> 100 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isobornyl acrylate 5888-33-5	LC50	0,704 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Propenamide, N,N-dimethyl- 2680-03-7	LC50	> 120 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	LC50	7,2 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxy-2- methylpropiophenone 7473-98-5	LC50	160 mg/l	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LC50	> 1 - 10 mg/l	48 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
p-Toluenesulphonyl isocyanate 4083-64-1	LC50	597 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Triphenyl phosphite 101-02-0	LC50	> 16 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)

# Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Mix of 2-hydroxyethyl acrylate and aliphatic isocyanate 264888-31-5	EC50	58 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isobornyl acrylate 5888-33-5	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Propenamide, N,N-dimethyl- 2680-03-7	EC50	> 120 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	EC50	26 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxy-2- methylpropiophenone 7473-98-5	EC50	> 119 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	> 10 - 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Triphenyl phosphite 101-02-0	EC50	> 1 - 5 mg/l	48 h	Daphnia sp.	OECD Guideline 202 (Daphnia sp. Acute

		Immobilisation Test)	

# Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isobornyl acrylate	NOEC	0,092 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
5888-33-5					magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	EC50	> 1.000 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Mix of 2-hydroxyethyl acrylate and aliphatic isocyanate 264888-31-5	EC50	> 100 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	NOEC	0,405 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	EC50	1,98 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Propenamide, N,N-dimethyl- 2680-03-7	EC50	> 400 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Propenamide, N,N-dimethyl- 2680-03-7	NOEC	50 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	EC50	0,17 mg/l	72 h	Scenedesmus sp.	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxy-2- methylpropiophenone 7473-98-5	EC50	1,95 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxy-2- methylpropiophenone 7473-98-5	NOEC	0,194 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	> 10 - 100 mg/l	72 h		OECD Guideline 201 (Alga, Growth Inhibition Test)

# Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hexane, 1,6-diisocyanato-,	EC 50	> 1.000 mg/l	3 h		OECD Guideline 209
homopolymer, V=2750-4250					(Activated Sludge,
mPas/23					Respiration Inhibition Test)
28182-81-2					
2-Propenamide, N,N-	EC50	> 1.000 mg/l	3 h	activated sludge, domestic	OECD Guideline 209
dimethyl-					(Activated Sludge,
2680-03-7					Respiration Inhibition Test)
Ethanone, 2,2-dimethoxy-1,2-	EC 50	> 100 mg/l	3 h		OECD Guideline 209
diphenyl-					(Activated Sludge,
24650-42-8					Respiration Inhibition Test)
2-Hydroxy-2-	EC 50	3 mg/l	3 h		OECD Guideline 209
methylpropiophenone					(Activated Sludge,
7473-98-5					Respiration Inhibition Test)
Diphenyl-2,4,6-	EC 50	> 1.000 mg/l	30 min		OECD Guideline 209
trimethylbenzoyl phosphine					(Activated Sludge,
oxide					Respiration Inhibition Test)
75980-60-8					
p-Toluenesulphonyl	EC 50	2.511 mg/l			OECD Guideline 209
isocyanate					(Activated Sludge,
4083-64-1					Respiration Inhibition Test)
Triphenyl phosphite	EC 50	> 100 mg/l	3 h		OECD Guideline 209
101-02-0					(Activated Sludge,
					Respiration Inhibition Test)
Phenyl bis(2,4,6-	EC 50	> 100 mg/l	3 h		OECD Guideline 209
trimethylbenzoyl)-phosphine					(Activated Sludge,
oxide					Respiration Inhibition Test)
162881-26-7					

# 12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2		aerobic	0 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Mix of 2-hydroxyethyl acrylate and aliphatic isocyanate 264888-31-5	not readily biodegradable.	aerobic	> 0 - < 60 %	28 d	OECD 301 A - F
Isobornyl acrylate 5888-33-5	not readily biodegradable.	aerobic	57 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
2-Propenamide, N,N-dimethyl- 2680-03-7	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2-Hydroxy-2- methylpropiophenone 7473-98-5	readily biodegradable	aerobic	90 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8			< 20 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
p-Toluenesulphonyl isocyanate 4083-64-1	readily biodegradable		98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7		aerobic	1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

# 12.3. Bioaccumulative potential

No data available.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	3,2			calculation	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Isobornyl acrylate 5888-33-5	37	56 h	24 °C	Danio rerio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	< 5				OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

# 12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Isobornyl acrylate 5888-33-5	4,52		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2-Propenamide, N,N-dimethyl- 2680-03-7	< 0,3	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	3,42		not specified
2-Hydroxy-2- methylpropiophenone 7473-98-5	1,62	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	5,8		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

#### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isobornyl acrylate 5888-33-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-Propenamide, N,N-dimethyl- 2680-03-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-Hydroxy-2-methylpropiophenone 7473-98-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

## Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances. The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes.

for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

# **SECTION 14: Transport information**

#### 14.1. UN number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

## 14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-
	Directle and 1.2 directle delay 1. and

Dimethoxy-1,2-diphenylethan-1-one)

RID ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-

Dimethoxy-1,2-diphenylethan-1-one)

ADN ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-

Dimethoxy-1,2-diphenylethan-1-one)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-

Dimethoxy-1,2-diphenylethan-1-one)

IATA Environmentally hazardous substance, liquid, n.o.s. (2,2-Dimethoxy-1,2-

diphenylethan-1-one)

#### 14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

#### 14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
ΙΔΤΔ	III

## 14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

# 14.6. Special precautions for user

ADR	not applicable
	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 % (2010/75/EC)

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

#### SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

# **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.