

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 10

SDS No.: 682880

V001.0 Revision: 28.01.2021 printing date: 03.02.2021

Replaces version from: -

LOCTITE ABLESTIK ABP 8142B

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE ABLESTIK ABP 8142B

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Sample only.

## 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

# 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (CLP):

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Germ cell mutagenicity Category 2

H341 Suspected of causing genetic defects.

Carcinogenicity Category 2

H351 Suspected of causing cancer.

# 2.2. Label elements

#### Label elements (CLP):

Hazard pictogram:



**Contains** Epoxycyclohexylethyltrimethoxysilane

Signal word: Warning

**Hazard statement:** H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

**Precautionary statement:** 

Prevention

P280 Wear protective gloves/protective clothing.

**Precautionary statement:** 

Response

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

#### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Siloxanes and Silicones, dimethyl,		1-< 5 %	Flam. Liq. 3
hydrogen-termi			H226
70900-21-9			
Epoxycyclohexylethyltrimethoxysilane	222-217-1	1-< 5 %	Skin Sens. 1B
3388-04-3			H317
			Muta. 2
			H341
			Carc. 2
			H351
			Aquatic Chronic 3
			H412
Dimethylhydropolysiloxane		1-< 5 %	Skin Irrit. 2
68037-59-2			H315
			Eye Irrit. 2
			H319
			STOT SE 3
			H335
1-Ethynylcyclohexanol	201-100-9	0,1-< 1 %	Skin Irrit. 2
78-27-3	01-2119966151-41		H315
			Acute Tox. 3; Dermal
			H311
			Acute Tox. 4; Oral
			H302
			Eye Irrit. 2
			H319

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

Prolonged or repeated contact may cause skin irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

water, carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

Silicon dioxide

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

### Additional information:

In case of fire, keep containers cool with water spray.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

## **6.2.** Environmental precautions

Do not empty into drains / surface water / ground water.

# 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed.

Refer to Technical Data Sheet

#### 7.3. Specific end use(s)

Sample only.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Occupational Exposure Limits**

Valid for

Great Britain

None

#### **Occupational Exposure Limits**

Valid for

Ireland

None

## **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

# Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance liquid

liquid

black Odor None

Odour threshold No data available / Not applicable

рΗ No data available / Not applicable Melting point No data available / Not applicable Solidification temperature No data available / Not applicable No data available / Not applicable Initial boiling point > 100 °C (> 212 °F); calculated Flash point Evaporation rate No data available / Not applicable Flammability No data available / Not applicable Explosive limits No data available / Not applicable Vapour pressure No data available / Not applicable Relative vapour density: No data available / Not applicable

Density 1,15 g/cm<sup>3</sup>

0

Bulk density No data available / Not applicable Solubility No data available / Not applicable

Solubility (qualitative) Insoluble

(Solvent: Water)

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

No data available / Not applicable
No data available / Not applicable
No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable
Oxidising properties

No data available / Not applicable

## 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Reacts with oxidants, acids and lyes

#### 10.2. Chemical stability

Stable under recommended storage conditions.

## 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

Excessive heat.

#### 10.5. Incompatible materials

See section reactivity.

#### 10.6. Hazardous decomposition products

No decomposition if used according to specifications.

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

# Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Epoxycyclohexylethyltri methoxysilane 3388-04-3	LD50	13.000 mg/kg	rat	

## Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Epoxycyclohexylethyltri methoxysilane 3388-04-3	LD50	6.700 mg/kg	rabbit	
1-Ethynylcyclohexanol 78-27-3	LD50	976 mg/kg	rabbit	not specified

#### Acute inhalative toxicity:

No data available.

## Skin corrosion/irritation:

No data available.

## Serious eye damage/irritation:

No data available.

# Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Epoxycyclohexylethyltri methoxysilane 3388-04-3	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

## Germ cell mutagenicity:

No data available.

## Carcinogenicity

No data available.

# Reproductive toxicity: No data available. STOT-single exposure: No data available.

# STOT-repeated exposure::

No data available.

#### **Aspiration hazard:**

No data available.

# **SECTION 12: Ecological information**

#### General ecological information:

Do not empty into drains / surface water / ground water.

## 12.1. Toxicity

## Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Epoxycyclohexylethyltrimetho	LC50	42,3 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish,
xysilane					Acute Toxicity Test)
3388-04-3					-

# Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Epoxycyclohexylethyltrimetho	EC50	58 mg/l	48 h	Daphnia magna	OECD Guideline 202
xysilane					(Daphnia sp. Acute
3388-04-3					Immobilisation Test)

## Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Epoxycyclohexylethyltrimetho	NOEC	16 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
xysilane					magna, Reproduction Test)
3388-04-3					

## Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Epoxycyclohexylethyltrimetho	NOEC	6 mg/l	72 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
xysilane				(new name: Pseudokirchneriella	Growth Inhibition Test)
3388-04-3				subcapitata)	
Epoxycyclohexylethyltrimetho	EC50	90 mg/l	72 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
xysilane				(new name: Pseudokirchneriella	Growth Inhibition Test)
3388-04-3				subcapitata)	· ·

#### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Epoxycyclohexylethyltrimetho	EC 50	> 100 mg/l	30 min		OECD Guideline 209
xysilane		_			(Activated Sludge,
3388-04-3					Respiration Inhibition Test)

#### 12.2. Persistence and degradability

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
Epoxycyclohexylethyltrimetho		aerobic	28 %	28 d	OECD Guideline 301 D (Ready
xysilane					Biodegradability: Closed Bottle
3388-04-3					Test)

#### 12.3. Bioaccumulative potential

No data available.

## 12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Epoxycyclohexylethyltrimetho	4,1	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
xysilane			Method)
3388-04-3			

## 12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

#### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

# Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

#### Waste code

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

# **SECTION 14: Transport information**

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation 1005/2009/EC):

Prior Informed Consent (PIC) (Regulation 649/2012/EC):

Persistent Organic Pollutants (POPs) (Regulation 2019/1021/EC):

Not applicable

Not applicable

EU. REACH, Annex XVII, Marketing and Use Restrictions (Regulation 1907/2006/EC): Not applicable

VOC content < 5 % (2010/75/EC)

# 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H341 Suspected of causing genetic defects.
- H351 Suspected of causing cancer.
- H412 Harmful to aquatic life with long lasting effects.

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.