



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 15

LOCTITE ABLESTIK 561K-1-004 known as Ablefilm 561K-1-004,
6 x 6

SDS No. : 377157
V004.0
Revision: 26.03.2018
printing date: 15.03.2021
Replaces version from: 04.11.2013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE ABLESTIK 561K-1-004 known as Ablefilm 561K-1-004, 6 x 6

Contains:

Butadiene, acrylonitrile polymer, carboxy-terminated, polymer with bisphenol A and epichlorohydrin
CP Bisphenol A Diglycidylether
4,4'-Isopropylidenediphenol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Epoxy adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000
Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:	
Signal word:	Warning
Hazard statement:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.
Precautionary statement:	P280 Wear protective gloves.
Prevention	
Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Self classification: product testing according to Classification, Labelling and Packaging Regulation EC/1272/2008, Annex 1, Part 4.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Adhesive

Base substances of preparation:

Epoxy resin

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Butadiene, acrylonitrile polymer, carboxy-terminated, polymer with bisphenol A and epichlorohydrin 68610-41-3		25- 50 %	Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1 H317 Aquatic Chronic 2 H411
CP Bisphenol A Diglycidylether 25036-25-3		0,1- < 1 %	Eye Irrit. 2 H319 Skin Irrit. 2 H315 Skin Sens. 1 H317 Aquatic Chronic 2 H411
4,4'-Isopropylidenediphenol 80-05-7	201-245-8 01-2119457856-23	0,1- < 0,3 %	Aquatic Chronic 2 H411 Eye Dam. 1 H318 Skin Sens. 1 H317 STOT SE 3 H335 Repr. 1B H360F ===== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC) EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact:

Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Remove sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed.

Keep frozen.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Epoxy adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL) (INHALABLE FRACTION)]		2	Time Weighted Average (TWA):	Indicative	ECLTV

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL) (INHALABLE DUST)]		10	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL) (INHALABLE FRACTION)]		2	Time Weighted Average (TWA):	Indicative	ECLTV

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
4,4'-Isopropylidenediphenol 80-05-7	aqua (freshwater)		0,018 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (marine water)		0,018 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (intermittent releases)		0,011 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sewage treatment plant (STP)		320 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sediment (freshwater)				1,2 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	sediment (marine water)				0,24 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	soil				3,7 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	oral				13,8 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Air						
4,4'-Isopropylidenediphenol 80-05-7	Predator						

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Acute/short term exposure - systemic effects		0,031 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Long term exposure - systemic effects		0,031 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Acute/short term exposure - systemic effects		2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Long term exposure - systemic effects		2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Long term exposure - systemic effects		0,002 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	General population	Inhalation	Long term exposure - systemic effects		1 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Long term exposure - local effects		2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Acute/short term exposure - local effects		2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - systemic effects		1 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Long term exposure - local effects		1 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - local effects		1 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Acute/short term exposure - systemic effects		0,002 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Long term exposure - systemic effects		0,004 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Acute/short term exposure - systemic effects		0,004 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	film solid
Odor	Off white
Odour threshold	Slight
	No data available / Not applicable
pH	8
()	
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	> 100 °C (> 212 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	Not applicable
Relative vapour density:	No data available / Not applicable
Density	No data available / Not applicable
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	Insoluble
(Solvent: Water)	
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with alcohols and amines.

Reacts with oxidants, acids and lyes

Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if stored and applied as directed.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Hydrocarbons

carbon oxides.

nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Butadiene, acrylonitrile polymer, carboxy- terminated, polymer with bisphenol A and epichlorohydrin 68610-41-3	LD50	> 2.000 mg/kg	rat	not specified
CP Bisphenol A Diglycidylether 25036-25-3	LD50	> 2.000 mg/kg	rat	not specified
4,4'- Isopropylidenediphenol 80-05-7	LD50	> 2.000 - < 5.000 mg/kg		
4,4'- Isopropylidenediphenol 80-05-7	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Butadiene, acrylonitrile polymer, carboxy- terminated, polymer with bisphenol A and epichlorohydrin 68610-41-3	LD50	> 2.000 mg/kg	rabbit	not specified
CP Bisphenol A Diglycidylether 25036-25-3	LD50	> 2.000 mg/kg	rabbit	not specified
4,4'- Isopropylidenediphenol 80-05-7	LD50	3.600 mg/kg	rabbit	not specified

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

No data available.

Serious eye damage/irritation:

No data available.

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
4,4'- Isopropylidenediphenol 80-05-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
4,4'- Isopropylidenediphenol 80-05-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
4,4'- Isopropylidenediphenol 80-05-7	NOAEL P 300 ppm		oral: feed	mouse	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

No data available.

Aspiration hazard:

No data available.

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

Self classification: product testing according to Classification, Labelling and Packaging Regulation EC/1272/2008, Annex 1, Part 4.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
CP Bisphenol A Diglycidylether 25036-25-3	LC50	3,1 mg/l	96 h	Pimephales promelas	not specified
4,4'-Isopropylidenediphenol 80-05-7	LC50	4,6 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol 80-05-7	NOEC	0,016 mg/l	444 d	Pimephales promelas	EPA OPP 72-5 (Fish Life Cycle Toxicity)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
CP Bisphenol A Diglycidylether 25036-25-3	EC50	1,8 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol 80-05-7	EC50	3,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4,4'-Isopropylidenediphenol 80-05-7	NOEC	0,17 mg/l	28 d	Americamysis bahia	EPA OPPTS 850.1350 (Mysid Chronic Toxicity Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
CP Bisphenol A Diglycidylether 25036-25-3	ErC50	11 mg/l	72 h	Scenedesmus capricornutum	not specified
4,4'-Isopropylidenediphenol 80-05-7	EC50	> 2,73 - 3,1 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	1,36 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
CP Bisphenol A Diglycidylether 25036-25-3	EC 50	> 100 mg/l			OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	> 320 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
CP Bisphenol A Diglycidylether 25036-25-3	not readily biodegradable.	not specified	12 %	28 day	not specified
4,4'-Isopropylidenediphenol 80-05-7	readily biodegradable	aerobic	89 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
4,4'-Isopropylidenediphenol 80-05-7	5,1 - 67	42 d	25 °C	Cyprinus carpio	other guideline:

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
CP Bisphenol A Diglycidylether 25036-25-3	3 - 5		not specified
4,4'-Isopropylidenediphenol 80-05-7	3,4	21,5 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
CP Bisphenol A Diglycidylether 25036-25-3	Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria
4,4'-Isopropylidenediphenol 80-05-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

- 14.1. UN number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H360F May damage fertility.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

