



# Aculon® NanoProof® 7.0 Hydrophobic/Oleophobic Treatment

## Product Information

**Aculon® NanoProof® 7.0** is a surface treatment capable of imparting hydrophobicity and oleophobicity to a wide variety of surfaces in a simple, one-step process. It is designed for multi-surface treatment on metals, semiconductors, and polymers. Aculon® NanoProof® 7.0 is typically applied by dip, dispense, or flow treatment and results in a hydro/oleophobic film that is resistant to chemical degradation. It is specifically designed to protect electronic circuitry from immersion in water.

Solids	Solvent	Color
<20% Proprietary Ingredient	Fluorosolvent	Pale yellow

Physical Properties of Formulation (all values @ 25°C)	
Viscosity*	Not Available
Boiling Point of Solvent	129°C
Flash Point	Not applicable
Environmental	Non toxic, non-ozone depleting
Shelf Life	2 Years (Unopened container)
Specific Gravity	1.63

\*Determined by Zahn Cup #1 testing

Physical Properties of Post Treatment Treatment	
Treatment Thickness (dip)	50 - 100 μM
Visible Light Transmission	TBD
Water Contact Angle	122
Oil Contact Angle	89

### Features

- Creates moisture barriers on coated parts
- Repels water, oil, and other liquid organic materials
- Adheres to a variety of surfaces ensuring protection of PCBs.
- Push-through conductivity within 2 hours
- Easy to apply
- RoHS compliant
- Contains no REACH SVHC compounds

### Application Ideas

- Coat PCB's for water proofing
- Impart repellency to consumer electronics

### Chemical Compatibility

#### Recommendation for tubing and plastics via application equipment

- Compatible with: Polyethylene terephthalate (PET), Polytetrafluoroethylene (PTFE), Polypropylene, Viton
- Avoid (Not Tested for Compatibility): HDPE, LDPE, Polyurethane, PVC, Tygon, Noryl, ABS, PP, Polyphenol ethylene ether, silicone, neoprene, EPM, and natural rubber

## Application Techniques

### Surface Preparation/ Cleaning:

Ensure that the surface is free of any grease, fingerprints, adhesive residues or dirt. This can be accomplished by first degreasing the surface with solvents or by rinsing with IPA. Depending on the sensitivity of your part to liquids Kyzen cleaners like Ionox I3416 or Cybersolv 141-R may be most appropriate for removing surface contamination. Contact Aculon if you are unsure what cleaner to use and we will recommend one best suited for your application. Substrates should be coated after cleaning as soon as possible to minimize the potential for recontamination.

### Treatment Application:

**Dispense:** Dispense product over the surface. Apply enough material to coat the surface. Allow excess material to drain.

**Dip:** Immerse the substrate in the solution for 20 seconds, air dry till solvent evaporated. Recommended dip containers are stainless steel, glass or aluminum. Plastic containers are likely to contaminate the treatment solution reducing performance.

**Drying:** Air dry at room temperature until the solvent evaporates. In some cases additional thermal curing (e.g. 100°C for 5 minutes) will speed solvent evaporation. Treatment will be deformable by touch during solvent evaporation, thus care should be taken when handling the part so as to not disturb the treatment in sensitive areas. After solvent evaporation treatment will be rigid.

**Masking:** Expect all masks to be compatible. For example: Techspray WonderMASK PX Peelable Solder Mask (2222-8SQ), Kapton Conformal Coating Tapes, Mylar tape, Polyimide

### Testing For Hydrophobicity:

Allow droplets of water to fall onto the surface, they should bead up to a contact angle >90°. If the surface is not hydrophobic clean the surface again and reapply.

### Safety, Handling, Storage, Shelf Life:

Store in -20°C freezer. Remove and allow to come to room temp just prior to use. Use thawed material within 2 days. See this product's MSDS for proper handling. This product does not contain any RoHS or REACH SVCH 168 compounds. When stored properly, product has a 2 year shelf life.

### For Additional Information:

To request additional product information or sales assistance, contact Aculon's Technical Team, at 858-350-9474. For information on other Aculon products, please visit our website at [www.aculon.com](http://www.aculon.com).

---

**Product Use:** All statements, technical information and recommendations contained in this document are based on tests or experience that Aculon believes to be dependable. However, many factors beyond Aculon's control can affect the use and effectiveness of an Aculon product in a particular use or application, including conditions under which the product is used and the time and conditions in which the product is expected to perform. Since these factors are exclusively within the user's knowledge and control, it is essential that the user evaluate the Aculon product to determine whether it is fit for a specific purpose and suitable for the user's method of application.

**Warranty and Liability:** Aculon makes no warranty or representation, expressed or implied, by operation of law or otherwise, as to the merchantability or fitness for a particular purpose of the goods arising out of a course of dealing, custom or usage of trade. Aculon shall not be liable for any defect in the goods sold hereunder and customer releases Aculon from any and all liability for negligence. Aculon will not be liable for consequential, incidental or any damages other than repair or replacement of defective good or refund of the purchase price paid for such defective goods.

Aculon • 11839 Sorrento Valley Road, Suite 901 • San Diego • California • 92121  
• Tel: 858-350-9474 • Email: [info@aculon.com](mailto:info@aculon.com)